

# CAM4xxx Series

## User Manual

Release 1.1



### **Copyright Statement**

No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise, without the prior written consent of Surveon Technology Inc.

### **Disclaimer**

Surveon Technology makes no representations or warranties with respect to the contents hereof and specifically disclaim any implied warranties of merchantability or fitness for any particular purpose. Furthermore, Surveon Technology reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation to notify any person of such revisions or changes. Product specifications are also subject to change without notice.

### **Trademarks**

Surveon and Surveon logo are trademarks of Surveon Technology Inc. Other names prefixed with “SMR” and “EMR” are trademarks of Surveon Technology Inc.

- Microsoft Windows and Windows are registered trademarks of Microsoft Corporation.
- Linux is a trademark of Linux Torvalds.
- Solaris and Java are trademarks of Sun Microsystems, Inc.

All other names, brands, products or services are trademarks or registered trademarks of their respective owners.

# Revision History

Version	Description	Date
1.0	Initial release: All the CAM4xxx series models are put into this manual; both hardware and software aspects are covered.	April 2012
1.1	New model: CAM4311/4371 are added.	June 2012

# Table of Contents

Copyright Statement .....	2
Revision History .....	3
Table of Contents .....	4
Safety Precautions .....	8
Device Site Recommendations.....	8
Chapter 1. Product Overview.....	9
1.1. Network Camera Introduction .....	9
1.2. Features and Benefits .....	9
1.3. Technical Specifications .....	11
Model List for CAM4xxx Series.....	11
Specifications for CAM41xx Series .....	11
Specifications for CAM42xx Series .....	13
Specifications for CAM431x Series .....	15
Specifications for CAM436x Series .....	17
Specifications for CAM437x Series .....	19
Chapter 2. Hardware Overview .....	21
2.1. Overview.....	21
Side View .....	21
Indoor: Fixed Lens (CAM4110/4210/4310/4311).....	21
Indoor: Varifocal Lens (CAM4220).....	21
Outdoor (CAM4160/4260/4360/4361/4365/4371) .....	21
Top View and Bottom View .....	22
Indoor (CAM4110/4210/4220/4310/4311) .....	22
Outdoor (CAM4160/4260/4360/4361/4365/4371) .....	22
2.2. Functions .....	23
2.3. Installation.....	27
Installing the Dome Camera .....	27
2.4. Camera Deployment .....	31

2.5. Before You Start.....	31
<b>Chapter 3. Connecting to the Network Camera.....</b>	<b>32</b>
3.1. Connecting with a Web Browser .....	33
Obtaining IP address through the IP Utility.....	33
Connecting to the Network Camera .....	33
Logging into the System.....	34
Installing Active X Components in Internet Explorer.....	34
Logging Out of the System .....	35
Using the Help Interface .....	35
3.2. Connecting with an RTSP Player .....	37
Connecting with a Mobile Device RTSP Player .....	37
<b>Chapter 4. Configuration through the Web Interface.....</b>	<b>38</b>
4.1. Interface Layout.....	40
Control Descriptions .....	41
4.2. Settings.....	43
General .....	43
Basic Settings .....	43
User Account.....	45
Date & Time .....	48
Network .....	50
Network Configuration .....	50
Port Settings .....	52
UpnP .....	54
Video & Audio Settings .....	55
Basic Settings .....	55
Image Appearance Settings .....	56
Image Appearance (for CAM4110/4160) .....	56
Image Appearance (for CAM4210/4220/4260) .....	60
Image Appearance (for CAM4310).....	63
Image Appearance (for CAM4311).....	67
Image Appearance (for CAM4360/4365) .....	70

Image Appearance (for CAM4361/4371) .....	75
Video Streams .....	80
Audio Settings .....	85
PTZ .....	86
Recording.....	87
Recording Basic Settings .....	87
Recorded File Management .....	88
Event Notification.....	90
Event Server .....	90
Motion Detection .....	92
Tampering Detection .....	94
DI & DO .....	95
Event Settings .....	97
System .....	103
MicroSD Card Management.....	103
System Status .....	104
System Log .....	105
Firmware Upgrade .....	106
Emergency Recovery Procedure.....	107
Resetting to Factory Default Settings .....	107
Export/Import & Reboot .....	109
<b>Chapter 5. Configuration through the IP Utility.....</b>	<b>110</b>
<b>5.1. Overview.....</b>	<b>112</b>
<b>5.2. Installing the IP Utility .....</b>	<b>112</b>
<b>5.3. IP Utility Basics .....</b>	<b>114</b>
Starting the IP Utility.....	114
IP Utility Main Screen.....	114
Exiting the IP Utility .....	114
<b>5.4. Camera Actions .....</b>	<b>115</b>
Search.....	115
Login .....	115

Properties .....	116
Delete from Tool .....	117
Select All .....	118
Rebooting Camera .....	118
Set IP.....	119
Link to Camera Web Interface .....	120
Link to Camera .....	120
Link to Camera User Manager .....	120
Clearing and Setting Status .....	121
Clear New Status .....	121
Set New Status.....	121
<b>5.5. Camera Group Actions.....</b>	<b>123</b>
Add Group.....	123
Delete Group.....	123
Rename Group.....	124
Move to Group .....	125
Copy to Group .....	126
<b>5.6. Configuration Settings.....</b>	<b>127</b>
Download Configuration.....	127
Update Configuration.....	128
<b>5.7. Firmware Actions .....</b>	<b>129</b>
Download Firmware.....	129
Update Firmware.....	129
<b>5.8. Focus Tool .....</b>	<b>131</b>

# Safety Precautions



## Electric Shock Warning

This equipment may cause electric shocks if not handled properly.

- Access to this equipment should only be granted to trained operators and maintenance personnel who have been instructed of, and fully understand the possible hazardous conditions and the consequences of accessing non-field-serviceable units such as the power supplies.
- The system must be unplugged before moving, or in the event that it becomes damaged.



## Reliable Grounding

Particular attention should be given to prepare reliable grounding for the power supply connection. It is suggested to use a direct connection to the branch circuit. Check for proper grounding before powering on the device.



## Overloading Protection

The device should be installed according to specifications. Provide a suitable power source with electrical overload protection. Do not overload the AC supply branch circuit that provides power to the device.



## ESD Precautions

Please observe all conventional anti-ESD methods while handling the device. The use of a grounded wrist strap and an anti-static work pad are recommended. Avoid dust and debris in your work area.

# Device Site Recommendations

The device should be installed according to specifications. This device should be operated at a site that is:

- Clean, dry, and free of excessive airborne particles.
- Well-ventilated and away from heat sources such as direct sunlight and radiators.
- Clear of vibration or physical shock.
- Away from strong electromagnetic fields produced by other devices.
- Available with properly grounded wall outlet for power. In regions where power sources are unstable, apply surge suppression.
- Available with sufficient space behind the device for cabling.

# Chapter 1. Product Overview

## 1.1. Network Camera Introduction

CAM4xxx series are professional network cameras that use Internet Protocol (IP) to transmit video streams and control signals over networks. Capable of operating over both LANs and WANs, they provide a complete budget-conscious remote surveillance solution that are ultra clear and highly integrated. CAM4xxx series combine a user-friendly interface and simplified installation with a powerful feature set to provide users an easy upgrade path to new digital surveillance system in a virtual environment. These highlights make CAM4xxx series ideal choices for environments that require remote surveillance or video transmission.

## 1.2. Features and Benefits

4xxx series IP camera is a cutting-edge digital video transmission device. It can compress and transmit real-time images of outstanding quality using a reasonable amount of bandwidth through a standard TCP/IP network. The following features make this IP camera an outstanding choice when building an intelligent IP surveillance system:

- **High Video Quality**

High image quality is essential in security surveillance applications. It is important to be able to clearly capture an incident in progress and identify persons or objects involved. A network camera gives exceptional video quality, even greater than that of traditional analog cameras, which means that more detail or larger areas can be covered.

- **H.264/MPEG-4/MJPEG Compression**

Motion JPEG, MPEG-4, and H.264 (also known as MPEG-4 Part 10/AVC), each employ different techniques to reduce the amount of data transferred and stored in a network video system. Network cameras that support multiple compression standards are ideal for maximum flexibility and integration possibilities.

- **Dual Streaming**

Dual-stream design enables simultaneous support of real-time video monitoring, video recording, or mobile viewing applications which require different resolutions, compression formats and frame rates.

- **MicroSD/SDHC card slot**

IP surveillance relies on network connectivity, making it susceptible to attacks on the network between the camera and recording facilities. With onboard recording capability, our network cameras can truly be online 24/7. The microSD/SDHC card slot design ensures sufficient recording capacity for an over-weekend period even at full frame rate and high resolution.

- **Tampering Detection**

This is an intelligent video analytics application available only in selected network cameras in the market. When a camera is manipulated in any way (e.g. accidental redirection, blocking, defocusing, spray-painted, covered or damaged), it can automatically trigger recording and alert notifications.

- **Power-over-Ethernet**

The built-in Power-over-Ethernet support reduces cabling and installation costs, and enables users to consolidate power facilities for higher reliability. With PoE, a camera can still operate in the event of a power failure if it is connected to a centralized backup power with an Uninterruptible Power Supply.

- **IR LED Illuminators**

With the built-in IR illuminators, the camera is capable of working in low light conditions, with a range up to 15m.

## 1.3. Technical Specifications

### Model List for CAM4xxx Series

CAM4110	D1 IP Fixed Dome
CAM4160	D1 D/N Outdoor IP Fixed Dome
CAM4210	1.3M IP Fixed Dome
CAM4220	1.3M D/N IP Fixed Dome
CAM4260	1.3M D/N Outdoor IP Fixed Dome
CAM4310	2M IP Fixed Dome
CAM 4311	2M D/N IP Fixed Dome
CAM4360	2M D/N Outdoor IP Fixed Dome
CAM4361	2M WDR D/N Outdoor IP Fixed Dome
CAM4365	3M D/N Outdoor IP Fixed Dome
CAM4371	2M WDR D/N Outdoor IP Fixed Dome

### Specifications for CAM41xx Series

Model Name	CAM4110	CAM4160
Description	D1 IP Fixed Dome	D1 D/N Outdoor IP Fixed Dome
Image Sensor	1/3.2" D1 progressive color CMOS	
Lens	4.2 mm, F1.8 (default)	2.8 - 11 mm varifocal lens, F1.4
SNR	50dB	
WDR	N/A	
Day/Night ICR	Dual Band Filter	Yes
IR LED	Yes (15M)	Yes (30M)
Min Illumination	0 Lux (IR LEDs on) 0.3 Lux @ F1.8 (Color)	
Iris Control	N/A	
Viewing Angle	Diagonal:89° Horizontal:71° Vertical:49.5°	Diagonal: 122°~35° Horizontal: 96°~28° Vertical: 72°~21°
Camera Angle Adjustment	Pan 0°~340° Tilt 30°~90°	
Pan/Tilt/Zoom Functionalities	N/A	
Shutter Time	1/60~1/10,000s	
Video Compression	H.264/MPEG-4/MJPEG	
Resolution	Up to 720 x 480	

Video FPS	30 fps at D1 (720 x 480) 30 fps at VGA (640 x 480) 30 fps at QVGA (320 x 240)	
Video Control	AGC (Auto Gain Control), AWB (Auto White Balance), AES (Auto Electronic Shutter), BLC (Back Light Compensation), Image Adjustment	
Video Stream	Dual stream at H.264, MPEG-4, and MJPEG simultaneously	
Bit Rate	64K ~ 6Mbps, VBR, CBR, controller frame rate and quality	
Intelligent Video	Motion Detection, Tampering Detection (blocked, redirected, defocused, or spray-painted)	
Video Jack	N/A	
Audio	2 Way Audio, Built-in MIC	2 Way Audio
Audio Compression	32KHz, ADPCM	
Audio Input/Output	3.5mm phone jack	
Alarm In/Out	2/1, terminal block	
Video Buffer	5 second pre-alarm, 30 second post-alarm	
Event Action	Send snapshot or video clip by FTP or email, record to NAS, record to local storage, trigger DO	
Supported Protocols	IPv4, ARP, TCP, UDP, ICMP, DHCP, NTP, DDNS, SMTP, FTP, HTTP, CIFS, PPPoE, UPnP, RTP, RTSP, RTCP, 3GPP	
Ethernet	10/100 Base-T / RJ45	
Local Storage	microSD/SDHC x 1 (Class 2/Class 4/Class 6)	
RS-485	1 (2 pin on terminal block)	
USB	N/A	
SDK	SDK 2.0	
OS	Microsoft Windows XP/Vista/7	
Browser	Microsoft IE 6.0 or above	
Software	VMS 2.4.1	
Temperature	Operation: -10~50°C (14~122°F) Storage: -30~60°C (-22~140°F)	Operation: -25~50°C (-13~122°F) Storage: -30~60°C (-22~140°F)
Humidity	5 to 90%	
Power	12VDC 1.5A ; PoE (IEEE 802.3af) with Class 3	
Power Consumption	Max. 7.5W	Max. 7.5W (w/o Heater) Max. 12W (w/ Heater)
Dimension	ø128.8mm x 98.6mm (H) ø5.07" x 3.88"(H)	ø144mm x 116mm (H) ø5.67" x 4.57"(H)
Weight	Net: 620g (1.37lb.) Gross: 1290g (2.85lb.)	Net: 1,260g (2.78lb.) Gross: 1,930g (4.27lb.)
Certification	Safety: LVD EMC: FCC, CE	Safety: LVD EMC: FCC, CE IP66

## Specifications for CAM42xx Series

Model Name	CAM4210	CAM4220	CAM4260
Description	1.3M IP Fixed Dome	1.3M D/N IP Fixed Dome	1.3M D/N Outdoor IP Fixed Dome
Image Sensor	1/3" 1.3 megapixel progressive scan CMOS		
Lens	4.2 mm, F1.8 (default)	2.8 - 11 mm varifocal lens, F1.4	
WDR	N/A		
Day/Night ICR	Dual Band Filter	Yes	
IR LED	Yes (15M)	Yes (30M)	
Min Illumination	0 Lux (IR LEDs on) 3 Lux @ F1.0 (Color)		
Iris Control	N/A	Manual IRIS	
Viewing Angle	Diagonal:89° Horizontal:71° Vertical:49.5°	Diagonal: 122°~35° Horizontal: 96°~28° Vertical: 72°~21°	
Camera Angle Adjustment	Pan 0°~340° Tilt 30°~90°		
Pan/Tilt/Zoom Functionalities	N/A		
Shutter Time	1/5~1/15,000 s		
Video Compression	H.264/MPEG-4/MJPEG		
Resolution	Up to 1280 x 1024		
Video FPS	15 fps at SXGA (1280 x 1024) 15 fps at HD720 (1280 x 720) 30 fps at VGA (640 x 480) 30 fps at QVGA (320 x 240)		
Video Control	AGC (Auto Gain Control), AWB (Auto White Balance), AES (Auto Electronic Shutter), BLC (Back Light Compensation), Image Adjustment		
Video Stream	Dual stream at H.264, MPEG-4, and MJPEG simultaneously		
Bit Rate	64K ~ 6Mbps, VBR, CBR, controller frame rate and quality		
Intelligent Video	Motion Detection, Tampering Detection (blocked, redirected, defocused, or spray-painted)		
Video Jack	N/A		
Audio	2/1	2 Way Audio, Built-in MIC	2 Way Audio
Audio Compression	32KHz, ADPCM		
Audio Input/Output	3.5mm phone jack		
Alarm In/Out	2/1, terminal block		
Video Buffer	5 second pre-alarm, 30 second post-alarm		

Event Action	Send snapshot or video clip by FTP or email, record to NAS, record to local storage, trigger DO		
Supported Protocols	IPv4, ARP, TCP, UDP, ICMP, DHCP, NTP, DDNS, SMTP, FTP, HTTP, CIFS, PPPoE, UPnP, RTP, RTSP, RTCP, 3GPP		
Ethernet	10/100 Base-T / RJ45		
Local Storage	microSD/SDHC x 1 (Class 2/Class 4/Class 6)		
RS-485	1 (2 pin on terminal block)		
USB	N/A		
SDK	SDK 2.0		
OS	Microsoft Windows XP/Vista/7		
Browser	Microsoft IE 6.0 or above		
Software	VMS 2.4.1		
Temperature	Operation: -10~50°C (14~122°F) Storage: -30~60°C (-22~140°F)		Operation: -25~50°C (-13~122°F) Storage: -30°C ~ 60°C (-22°F~140°F)
Humidity	5 to 90%		
Power	12VDC 1.5A ; PoE (IEEE 802.3af) with Class 3		
Power Consumption	Max. 7.5W		Max. 7.5W (w/o Heater) Max. 12W (w/ Heater)
Dimension	ø128.8mm x 98.6mm (H) ø5.07" x 3.88"(H)	ø128.8mm x 115mm (H) ø5.07" x 4.52" (H)	ø144mm x 116mm (H) ø5.67" x 4.57"(H)
Weight	Net: 620g (1.37lb.) Gross: 1290g (2.85lb.)	Net: 700g (1.54lb.) Gross: 1370g (3.00lb.)	Net: 1,260g (2.78lb.) Gross: 1,930g (4.27lb.)
Certification	Safety: LVD EMC: FCC, CE		Safety: LVD EMC: FCC, CE IP66

## Specifications for CAM431x Series

Model Name	CAM4310	CAM4311
Description	2M IP Fixed Dome	2M D/N IP Fixed Dome
Image Sensor	1/2.7" 2 megapixel progressive scan CMOS	
Lens	4.2 mm, F1.8 (default)	4.0 mm, F2.0
SNR	48dB	
WDR	N/A	Yes
Day/Night ICR	N/A	Yes
IR LED	N/A	Yes (10M)
Min Illumination	0.5 Lux @ F1.0 0.5 Lux @ F1.0 (Color)	0.01 Lux @ F1.2 (B/W) 0.1 Lux @ F1.2 (Color)
Iris Control	N/A	
Viewing Angle	Diagonal:89° Horizontal:71° Vertical:49.5°	Diagonal: 101.7° ° Horizontal: 87.7° ° Vertical: 48°
Camera Angle Adjustment	Pan 0°~340° Tilt 30°~90°	
Pan/Tilt/Zoom Functionalities	N/A	
Shutter Time	1/30~1/50,000 s	
Video Compression	H.264/MPEG-4/MJPEG	
Resolution	Up to 1920 x 1080	
Video FPS	25 fps at 1080P (1920 x 1080) 30 fps at SXGA (1280 x 1024) 30 fps at HD720 (1280 x 720) 30 fps at D1 (720 x 480) 30 fps at VGA (640 x 480) 30 fps at QVGA (320 x 240)	25 fps at 1080P (1920 x 1080) 30 fps at SXGA (1280 x 1024) 30 fps at HD720 (1280 x 720) 30 fps at D1 (720 x 480) 30 fps at VGA (640 x 480) 30 fps at QVGA (320 x 240)
Video Control	AGC (Auto Gain Control), AWB (Auto White Balance), AES (Auto Electronic Shutter), BLC (Back Light Compensation), HLC (High Light Compensation), 3D Noise Reduction, Defog, Image Adjustment	
Video Stream	Dual stream at H.264, MPEG-4, and MJPEG simultaneously	
Bit Rate	64K ~ 6Mbps, VBR, CBR, controller frame rate and quality	
Intelligent Video	Motion Detection	
Video Jack	N/A	
Audio	2 Way Audio, Built-in MIC	N/A
Audio Compression	32KHz, ADPCM	

Audio Input/Output	3.5mm phone jack
Alarm In/Out	N/A
Video Buffer	5 second pre-alarm, 30 second post-alarm
Event Action	Send snapshot or video clip by FTP or email, record to NAS, record to local storage, trigger DO
Supported Protocols	IPv4, ARP, TCP, UDP, ICMP, DHCP, NTP, DDNS, SMTP, FTP, HTTP, CIFS, PPPoE, UPnP, RTP, RTSP, RTCP, 3GPP
Ethernet	10/100 Base-T/RJ45
Local Storage	microSD/SDHC x 1 (Class 2/Class 4/Class 6)
RS-485	1 (2 pin on terminal block)
USB	N/A
SDK	Surveon SDK 2.0
OS	Microsoft Windows XP/Vista/7
Browser	Microsoft IE 6.0 or above
Software	Surveon VMS 2.4.1
Temperature	Operation: -10~50°C (14~122°F) Storage: -30~60°C (-22~140°F)
Humidity	5 to 90%
Power	12VDC 1.5A ; PoE (IEEE 802.3af) with Class 3
Power Consumption	Max. 7.5W
Dimension	ø128.8mm x 98.6mm (H) ø5.07" x 3.88"(H)
Weight	Net: 620g (1.37lb.) Gross: 1290g (2.85lb.)
Certification	Safety: LVD EMC: FCC, CE

## Specifications for CAM436x Series

Model Name	CAM4360	CAM4361	CAM4365
Description	2M D/N Outdoor IP Fixed Dome	2M WDR D/N Outdoor IP Fixed Dome	3M D/N Outdoor IP Fixed Dome
Image Sensor	1/2.7" 2 megapixel progressive scan CMOS		1/2.8" 3 megapixel SONY low light CMOS
Lens	3~10 mm motor lens, F1.3	2.8~11 mm varifocal lens, F1.4	3~10 mm motor lens, F1.3
SNR	48dB		
WDR	N/A	Yes	
Day/Night ICR	Yes		
IR LED	Yes (15M)	Yes (20M)	Yes (15M)
Min Illumination	0 Lux (IR LEDs on) 0.5 Lux @ F1.0 (Color)	0.01 Lux @ F1.2 (B/W) 0.1 Lux @ F1.2 (Color)	0 Lux (IR LEDs on) 0.1 Lux @ F1.2 (Color)
Iris Control	DC drive		
Viewing Angle	Diagonal: 122°~35° Horizontal: 96°~28° Vertical: 72°~21°	Diagonal: 99°~37.3° Horizontal: 79.3°~29.8° Vertical: 59.5°~22.4°	Diagonal: 122°~35° Horizontal: 96°~28° Vertical: 72°~21°
Camera Angle Adjustment	Pan 0°~340° Tilt 30°~90°		
Pan/Tilt/Zoom Functionalities	N/A		
Shutter Time	1/7.5 ~ 1/100,000s	1/30~1/50,000s	1/7.5 ~ 1/100,000s
Video Compression	H.264/MPEG-4/MJPEG		
Resolution	Up to 1920 x 1080		Up to 2048 x 1536
Video FPS	25 fps at 1080P (1920 x 1080) 30 fps at SXGA (1280 x 1024) 30 fps at HD720 (1280 x 720) 30 fps at D1 (720 x 480) 30 fps at VGA (640 x 480) 30 fps at QVGA (320 x 240)		15 fps at QXGA (2048 x 1536) 25 fps at 1080P (1920 x 1080) 30 fps at SXGA (1280 x 1024) 30 fps at HD720 (1280 x 720) 30 fps at D1 (720 x 480) 30 fps at VGA (640 x 480) 30 fps at QVGA (320 x 240)
Video Control	AGC (Auto Gain Control), AWB (Auto White Balance), AES (Auto Electronic Shutter), BLC (Back Light Compensation), HLC (High Light Compensation), 3D Noise Reduction, Defog, Image Adjustment	AGC (Auto Gain Control), AWB (Auto White Balance), AES (Auto Electronic Shutter), BLC (Back Light Compensation), HSLC (High Suppression Backlight Compensation), 3D Noise Reduction, Defog, Image Adjustment	AGC (Auto Gain Control), AWB (Auto White Balance), AES (Auto Electronic Shutter), BLC (Back Light Compensation), Image Adjustment
Video Stream	Dual stream at H.264, MPEG-4, and MJPEG simultaneously		
Bit Rate	64K ~ 6Mbps, VBR, CBR, controller frame rate and quality		

Intelligent Video	Motion Detection	Motion Detection, Tampering Detection (blocked, redirected,	Motion Detection
Video Jack	N/A	Yes (BNC)	N/A
Audio	2 Way Audio	N/A	2 Way Audio
Audio Compression	32KHz, ADPCM		
Audio Input/Output	3.5mm phone jack		
Alarm In/Out	2/1, terminal block	N/A	2/1, terminal block
Video Buffer	5 second pre-alarm, 30 second post-alarm		
Event Action	Send snapshot or video clip by FTP or email, record to NAS, record to local storage, trigger DO		
Supported Protocols	IPv4, ARP, TCP, UDP, ICMP, DHCP, NTP, DDNS, SMTP, FTP, HTTP, CIFS, PPPoE, UPnP, RTP, RTSP, RTCP, 3GPP		
Ethernet	10/100 Base-T / RJ45		
Local Storage	microSD/SDHC x 1 (Class 4/Class 6 only)		
RS-485	1 (2 pin on terminal block)	N/A	1 (2 pin on terminal block)
USB	N/A		
SDK	SDK 2.0		
OS	Microsoft Windows XP/Vista/7		
Browser	Microsoft IE 6.0 or above		
Software	VMS 2.4.1		
Temperature	Operation: -25~ 50°C (-13~122°F) Storage: -30~60°C (-22~140°F)		
Humidity	5 to 90%		
Power	12VDC 1.5A ; PoE (IEEE 802.3af) with Class 3		
Power Consumption	Max. 7.5W (w/o Heater) Max. 12W (w/ Heater)	Max. 8W (w/o Heater ) Max. 35W (w/ Heater )	Max. 7.5W (w/o Heater) Max. 12W (w/ Heater)
Dimension	ø144mm x 116mm (H) ø5.67" x 4.57"(H)		
Weight	Net: 1,260g (2.78lb.) Gross: 1,930g (4.27lb.)		
Certification	Safety: LVD EMC: FCC, CE IP66		

## Specifications for CAM437x Series

Model Name	<b>CAM4371</b>
Description	2M WDR D/N Outdoor IP Fixed Dome
Image Sensor	1/2.8" 2 megapixel SONY Exmor CMOS (CAM4371)
Lens	3-9 mm moto lens, F1.2
SNR	48dB
WDR	Yes
Day/Night ICR	Yes
IR LED	Yes (20M)
Min Illumination	0.01 Lux @ F1.2 (B/W) 0.1 Lux @ F1.2 (Color)
Iris Control	DC drive
Viewing Angle	Diagonal: 148.4° - 43.8° Horizontal: 121.2° - 38.1° Vertical: 62.1° - 21.3° (CAM4371)
Camera Angle Adjustment	Pan 0°-340° Tilt 30°-90°
Pan/Tilt/Zoom Functionalities	N/A
Shutter Time	1/30~1/50,000s
Video Compression	H.264/MPEG-4/MJPEG
Resolution	Up to 1920 x 1080
Video FPS	25 fps at 1080P (1920 x 1080) 30 fps at SXGA (1280 x 1024) 30 fps at HD720 (1280 x 720) 30 fps at D1 (720 x 480) 30 fps at VGA (640 x 480) 30 fps at QVGA (320 x 240)
Video Control	AGC (Auto Gain Control), AWB (Auto White Balance), AES (Auto Electronic Shutter), BLC (Back Light Compensation), HSLC (High Suppression Backlight Compensation), 3D Noise Reduction, Defog, Image Adjustment
Video Stream	Dual stream at H.264, MPEG-4, and MJPEG simultaneously
Bit Rate	64K ~ 6Mbps, VBR, CBR, controller frame rate and quality
Intelligent Video	Motion Detection, Tampering Detection (blocked, redirected,
Video Jack	Yes (BNC)


Audio	2 Way Audio
Audio Compression	32KHz, ADPCM
Audio Input/Output	3.5mm phone jack
Alarm In/Out	N/A
Video Buffer	5 second pre-alarm, 30 second post-alarm
Event Action	Send snapshot or video clip by FTP or email, record to NAS, record to local storage, trigger DO
Supported Protocols	IPv4, ARP, TCP, UDP, ICMP, DHCP, NTP, DDNS, SMTP, FTP, HTTP, CIFS, PPPoE, UPnP, RTP, RTSP, RTCP, 3GPP
Ethernet	10/100 Base-T / RJ45
Local Storage	microSD/SDHC x 1 (Class 2/Class 4/Class 6)
RS-485	N/A
USB	N/A
SDK	SDK 2.0
OS	Microsoft Windows XP/Vista/7
Browser	Microsoft IE 6.0 or above
Software	VMS 2.4.1
Temperature	Operation: -25~ 50°C (-13~122°F) Storage: -30~60°C (-22~140°F)
Humidity	5 to 90%
Power	12VDC 1.5A ; PoE (IEEE 802.3af) with Class 3
Power Consumption	Max. 8W (w/o Heater ) Max. 35W (w/ Heater )
Dimension	ø144mm x 116mm (H) ø5.67" x 4.57"(H)
Weight	Net: 1,260g (2.78lb.) Gross: 1,930g (4.27lb.)
Certification	Safety: LVD EMC: FCC, CE IP66

# Chapter 2. Hardware Overview


## 2.1. Overview

### Side View


Indoor: Fixed Lens (CAM4110/4210/4310/4311)



Indoor: Varifocal Lens (CAM4220)




Outdoor (CAM4160/4260/4360/4361/4365/4371)




# Top View and Bottom View

Indoor (CAM4110/4210/4220/4310/4311)




Outdoor (CAM4160/4260/4360/4361/4365/4371)




1. Status LED Indicator	2. Reset Button	3. MicroSD/SDHC Card Slot
-------------------------	-----------------	---------------------------


## 2.2. Functions



Indoor



Outdoor



Please look into the following table for cable options:

	CAM4110	CAM4160	CAM4210	CAM4220	CAM4260
Audio In/Out Connector	v	v	v	v	v
Network Connector	v	v	v	v	v
Power Connector	v	v	v	v	v
I/O Terminal Connector	v	v	v	v	v
Video Out Connector					

	CAM4310	CAM4311	CAM4360	CAM4361	CAM4365	CAM4371
Audio In/Out Connector	Optional		Optional		Optional	
Network Connector	v	v	v	v	v	v
Power Connector	v	v	v	v	v	v
I/O Terminal Connector	Optional		Optional		Optional	
Video Out Connector				v		v

## 1. Audio In/Out Connector

Audio In/Out are both for 3.5mm jacks. Audio-in provides for an external mono microphone. Audio out can be connected to a public address system or an active speaker with a built-in amplifier. A pair of headphones can also be attached.

**Note:** Built-in microphone can also be used for certain models. Please refer to *Audio Setting* section for details.

## 2. Status LED Indicator

The LED will light up after the camera has successfully completed the boot process. The Status LED indicator in the rear of the camera can be set to light whenever the unit is accessed, or be shut off.

Status LED (rear)	Green	Shows steady green for normal operation, flashing when the camera is accessed. Note: The Status LED can be configured to be unlit.
	Amber	Steady during startup, reset to factory default or when restoring settings.
		Flashes every 0.2 sec during firmware upgrade. (On:0.2 sec, Off: 0.2 sec) Note: Startup or reboot may have failed if the status LED shows steady amber for over 1 minute.
	Unlit	No network connection.

## 3. Video Out Connector (CAM4361 only)

Video Out Connector is used for connecting monitors with BNC ports.

## 4. Reset Button

Pressing the reset button will restore the camera to its factory default settings, as described in *Resetting to the Factory Default Settings*.

## 5. microSD/SDHC Card Slot

The microSD/SDHC card slot can be used for local recording and firmware upgrade.

**Note:** Apacer 4GB Class 6/Transcend 8GB Class 6/Kingston 16GB Class 2, SanDisk 16GB Class 2/SanDisk 32GB Class 4 MicroSDHC card are recommended, since they have passed the SD Card QVL (Qualified Vender List) test.

## 6. Network Connector

The camera connects to the network via a standard RJ-45 network connector. The camera detects the speed of the local network (10/100BaseT). The camera also supports PoE (Power-over-Ethernet), and can be powered directly through the network cable.

## 7. Power Connector

The power connector is provided for solutions without PoE.

## 8. I/O terminal Connector


The I/O terminal connector provides an RS-485 interface, one transistor output, two digital inputs, and connection points for auxiliary DC power and GND.

The I/O terminal connector provides the interface to:

- 1 transistor output - For connecting external devices such as relays and LEDs. Devices can be activated by Output buttons on the Live View page or by an Event. The output will show as active (in Event Configuration > Port Status) if the alarm device is activated.
- 2 digital inputs - An alarm input for connecting devices that can toggle between an open and closed circuit, for use with devices such as PIRs, door/window contacts, glass break detectors, etc. When a signal is received the state changes and the input becomes active (shown under Event Configuration > Port Status).
- Auxiliary power and GND

GND	Pin 1	Ground	Description
12V Auxiliary DC Power (not to power this camera)	Pin 2	Electrically connected in parallel with the connector for the power supply, this pin provides an auxiliary connector for main power to the unit. This pin can also be used to power auxiliary equipment with a maximum current of 100mA.	Voltage: 12V DC, Max: 1.2W
DI1(Digital Input)	Pin 3	Connect to GND to activate, or leave floating (or unconnected) to	Must not be exposed to voltages greater than 30V DC

		deactivate.	
DI2 (Digital Input)	Pin 4	Connect to GND to activate, or leave floating (or unconnected) to deactivate.	Must not be exposed to voltages greater than 30V DC
DO(Digital Output)	Pin 5	Uses an open-collector NPN transistor with the emitter connected to the GND pin. If used with an external relay, a diode must be connected in parallel with the load, for protection against voltage transients.	Max load = <100mA Max voltage = 24V DC (to the transistor)
RS-485A	Pin 6	Data transmission connector for control of external devices. (ex. Pan/Tilt scanners)	Tx
RS-485B	Pin 7	Data transmission connector for control of external devices. (ex. Pan/Tilt scanners)	Tx




## 2.3. Installation

### Installing the Dome Camera


#### Indoor

Screw Hole Indicator Sticker



#### Outdoor

Screw Hole Indicator Sticker




1. Use screw hole indicator sticker to mark the desired camera position on the ceiling.
2. Make one cable entry hole and 3 or 4 screw holes on the ceiling with the electrical drill.
3. **(Indoor)** Remove the base plate from the bottom of the camera assembly.  
**(Outdoor)** Use the provided L-type hex wrench to unscrew the cover of the camera.
4. **(Indoor)** Align the base plate with the sticker and turn it clockwise to secure it on top of the sticker.


**(Outdoor)** Align the housing with the sticker and fasten the screws to secure the housing on top of the sticker.

5. Thread the multiple connector interface cable through the cable entry hole on the base plate or housing.

**(Outdoor - Optional)** The default cable entry hole is located on bottom of the camera. If the installation requires use of the lateral-side cable hole, remove the cap from the lateral-side cable hole. Disconnect the cable from the board entirely, and reinsert it through the lateral cable hole. Reconnect the cable to the camera.




6. Connect the camera to network with the network connector.
7. Connect the power connector to a power outlet.
8. The status LED indicator will blink amber to indicate the boot-up sequence has started. Wait until the LED is in a steady green state, indicating the camera boot-up is complete.
9. **(Indoor)** Reattach the camera assembly to the base plate.
10. **(Indoor)** Remove the camera cover by twisting it counterclockwise. Adjust the desired view angle as needed. On models equipped with varifocal lenses, you may also adjust the zoom and focus by unscrewing the corresponding puller, adjusting and then re-tightening the puller. After adjustments are complete, reinstall the camera cover and secure it with the included retaining screw.



**Outdoor)** Unscrew the zoom puller on the lens and adjust the desired view angle as needed. Re-tighten the zoom puller. Unscrew the focus puller on the lens and adjust the focus as required. Re-tighten the focus puller and


reinstall the camera cover.



**Note:** (1) Cover removal is not required on models with motorized lenses (CAM4360/4365/4371). (2) Please check the live view after the camera is logged in.

## Installing the Dome Camera with the Mounting Bracket (Optional)


1. **(Indoor)** Remove the base plate from the bottom of the camera.




Base Plate

**(Outdoor)** Use the provided L-type hex wrench to unscrew the cover of the camera.


2. **(Indoor)** Align the base plate with the mounting bracket and fasten screws to secure the plate on the bracket.




3. Fasten the mounting bracket to the wall at the desired camera location.  
If required, use the provided thread-spaces on the side of the bracket for wires.
4. **(Indoor)** Thread the multiple connector interface cable and any other input or output cables for sensors or alarms through the base plate hole and the back of the mounting bracket.




5. **(Indoor)** Reattach the camera assembly to the base plate.



**(Outdoor)** Align the housing with the mounting bracket and fasten screws to secure the housing on the bracket.



## 2.4. Camera Deployment



## 2.5. Before You Start

Please prepare a PC with Windows (XP or above) and web browsers (Internet Explorer 6.0 or above) installed.

# Chapter 3. Connecting to the Network Camera

This section demonstrates how to connect to the network camera through two methods:


- Web Browser - A simple web-based interface. Internet Explorer is the recommended web browser for use with network cameras, and our examples will be from this browser. Usage on other browsers will be similar.
- RTSP Player - These include common streaming media players, such as *RealPlayer* or *Quicktime Player*. These players can provide live view of the camera using the Real-Time Streaming Protocol (RTSP).

## 3.1. Connecting with a Web Browser

### Obtaining IP address through the IP Utility

The IP address can be obtained using the IP Utility in your product CD:

1. Double click Start SearchToolInstall.exe to begin the utility installation.
2. After the installation is complete, click the **Auto Search** button or click **Camera > Search** in the menus.



The camera search will begin, and a status bar will display the search progress.

3. The details of the camera will display after the search is finished.


Details							
	Number	Name	IP	Model	MAC	Status	NetMask
<input type="checkbox"/>	1	CAM2320	172.18.6.147	CAM2320	00D02360022F	New	255.255.254.0
<input type="checkbox"/>	2	CAM2311	172.18.7.61	CAM2311	000C0CA006AA	New	255.255.254.0
<input type="checkbox"/>	3	CAM3365	172.18.6.80	CAM3365	00D02360022C	New	255.255.254.0
<input type="checkbox"/>	4	CAM1300	172.18.6.215	CAM1300	000C0CA006F1	New	255.255.254.0

**Note:** (1) The search may take up to 2 minutes, depending on your network configuration. (2) If your network does not have DHCP service, the default IP address is 192.168.88.10.

### Connecting to the Network Camera

Launch the web browser (Microsoft ® Internet Explorer 6.0 or higher is recommended). Enter the IP address of the network camera in the address bar of your browser and press enter.

You can also Click the **Link to Camera** button or click **Camera> Link to Camera** in the IP Utility menu bar. The camera's live view webpage will open in a browser window.



## Logging into the System

The following information will prompt for logging in:

- **Username** - The username for the domain. **Default is always *admin*.**
- **Password** - The password for the domain. **Default is always *admin*.**

Click OK.


## Installing Active X Components in Internet Explorer

You may be prompted to install ActiveX® components when accessing the network camera's Live View page; click **Yes** when prompted. You will be able to access the camera after installation is completed. Under Windows, this action may require administrator privileges.

If the dialog box suggests that you are not allowed to install ActiveX components, try resolving the problem using the following steps:

1. In Internet Explorer, open Tools> Internet Options> Security. Click the Custom level button.

2. Search for *Download signed ActiveX controls*. Under this heading select **Prompt** and then click **OK**.



3. Continue installing the Active X components.
4. After installing ActiveX, go to **Tools > Internet Options > Trusted Websites > Sites** and add the IP Address of the camera.

## Logging Out of the System

Logging off of the camera can be performed by closing the browser window.


Users can also choose to click the **Logout** link located at the top of the screen.



## Using the Help Interface

While using the web interface, you may click on the **Help** link located under the title bar. This will bring up a pop-up containing the IP Camera Help manual. This provides simple explanation of the camera settings, and will automatically open to the page relevant to your current screen.


The help manual is organized so that it matches the system menus, with sections corresponding to each settings menu and the Live-view window.



## 3.2. Connecting with an RTSP Player

Connections through RTSP Media Players such as *Real Player* and *QuickTime Player* are supported. We will use Real Player as an example in this section.

1. Launch Real Player.
1. Select **File > Open URL**, to open a URL dialog box.
2. Enter the camera URL in the address bar.



**Note:** The format for RTSP is: `rtsp://<IP Address>/<Access>`, where `<Access>` can be found at **Settings > Network > Port Settings > RTSP Setting**. By default the `<Access>` value should be `stream1` and `stream2`.

3. Click **OK**, the stream should begin playing.

## Connecting with a Mobile Device RTSP Player

In order to access streaming video on 3GPP mobile devices, please make sure the network camera is already online and connected to the Internet. In the **IP** field under the *IP Address* section of the window, enter the IP address of the IP camera.

1. Change the settings under **Settings > Video & Audio > Stream2**: Set the image format as MJPEG4, resolution as QVGA (320x240 or below, and constant bit rate as 128 Mbps or below.
2. Launch the RTSP Player on the 3GPP mobile device and enter the URL address for the camera. The video should start playing.

**Note:** The format for RTSP is: `rtsp://<IP Address>/<Access>`, where `<Access>` can be found at **Settings > Network > Port Settings > RTSP Setting**. By default the `<Access>` value should be `stream1` and `stream2`.

# Chapter 4. Configuration through the Web Interface

Camera configurations can be done through web interface and IP Utility.

\*\*For web interface, please look into [this chapter](#); for IP Utility, please refer to [Chapter 5](#).

		Web Interface	IP Utility
General	Basic Settings	V	X
	User Account	V	X
	Date & Time	V	X
Network	Network Configuration	V	Set IP Only
	Port Settings	V	X
	UpnP	V	X
	Wifi Setting (CAM1300/1311 Only)	V	X
Video & Audio Settings	Basic Settings	V	X
	Image Appearance Settings	V	X
	Video Streams	V	X
	Audio Settings	V	X
PTZ	RS-485 Settings/PTZ Settings	V	X
Recording	Recording Basic Settings	V	X
	Recorded File Management	V	X
Event Notification	Event Server	V	X
	Motion Detection	V	X
	Tampering Detection	V	X
	DI & DO	V	X
	Event Settings	V	X
System	MicroSD Card Management	V	X
	System Status	V	V
	System Log	V	X
	Firmware Upgrade	V	V
	Resetting to Factory Default Settings	V	X

	Export/Import	V	X
	Reboot	V	V
Camera Search		X	V
Login		V	V
Properties		X	V
Delete from Tool		X	V
Clearing and Setting Status		X	V
Camera Group Actions		X	V
Configuration Settings		X	V
Focus Tool		X	V

## 4.1. Interface Layout








This section demonstrates the layout of the network camera's main interface.








The 4 main areas on the interface are:



1. **Menu Bar** - The links on this bar allow users to toggle between live-view and settings screens, as well as logout and pull up the help menu.
2. **Live View Controls** - These controls allow users to configure the live view streams and camera live view functionality.
3. **Button Bar** - These controls allow the user to quickly access common features such as live view window resizing, video and still frame capture, interface language, and audio controls.
4. **Live View Window** - This portion of the screen displays the stream selected in the **Live View Control** section of the web interface.

## Control Descriptions

Control	Description
	<b>Adjust Window Size:</b> When clicked, the display window size can be adjusted manually to fit the screen. The screen size changes back to the actual image size (resolution).
	<b>Full-Screen:</b> Goes to full-screen when clicked; press “ESC” to return to windowed view.
	<b>Image Capture:</b> When clicked, captures the current screen as an image in a new pop-up window. The location for saving the image can be changed under <a href="#">Settings &gt; Recording &gt; Recording Basic Settings</a> . The file name is set to “Camera Name”+yyyymmdd_hhmmss (the Camera Name can be changed under <a href="#">Settings &gt; General &gt; Basic Settings</a> ).
	<b>Manual Record:</b> When clicked, records the current live video. Stops recording when clicked again. The location for storing the recording can be changed under <a href="#">Settings &gt; Recording &gt; Recording Basic Settings</a> .
	<b>Audio-In:</b> Turned off by default; clicking once allows audio to be transmitted from a local microphone to the camera. Clicking again stops audio transmission. Multiple users may access the live view page and receive audio from the camera, but only one user at once is allowed to send audio to the camera.
	<b>Mute:</b> Mutes the audio captured by the camera when clicked, un-mutes the audio when clicked again.
	<b>Volume:</b> Sets to the current computer volume; Dragging the slider adjusts the volume.

Control	Description
	<b>Language:</b> Sets the UI language. Available languages include English, Simplified Chinese, and Traditional Chinese.
	<b>Streams:</b> Allows users to choose which camera stream to view. The indicator above the stream will turn light green when the stream is selected.
	<b>Video Format:</b> Sets the compression format for the current stream. Available formats are H.264, MPEG4, and MJPEG.
	<b>Image size (resolution):</b> Sets the resolution of the stream currently selected. Sets the resolution of the stream currently selected. Options are available for each stream: 1536P (2048 x 1536), 1080P (1920 x 1080), SXGA (1280 x 1024), 720P (1280 x 720), VGA (640 x 480), QVGA (320 x 240) for stream 1 and VGA (640 x 480), QVGA (320 x 240), QQVGA (160 x 120) for stream 2.
	<b>Digital Zoom:</b> When clicked, activates digital zoom in the current live-view stream. 2 options are available when clicked: <div style="margin-top: 10px;">  <b>Zoom In</b> </div> <div style="margin-top: 10px;">  <b>Zoom Out</b> </div>

## 4.2. Settings

Camera settings may be changed by clicking on the **Settings** link located in the title bar. This will bring up a menu list of configuration menus for all major camera settings.

### General

General setting menus are found under **Settings > General**.

#### Basic Settings

The screenshot shows the 'Basic Settings' window of a camera's web interface. The top navigation bar includes 'Live View', 'Settings', 'Logout', and 'Help'. The user is logged in as 'admin' on '2010-07-23 13:34:08'. The left sidebar shows a tree view with 'General' expanded, containing 'Basic Settings', 'User Account', and 'Date & Time'. Other categories like 'Network', 'Video & Audio', 'PTZ', 'Recording', 'Event Notification', and 'System' are also listed. The main content area is titled 'General > Basic Settings' and contains three sections: 'Host Name' with a text field containing 'CAM2100 00:d0:23:0f:fd:72'; 'Camera Name' with a text field containing 'CAM2100' and a note '(Valid characters: A-Z, a-z, 0-9, ., space)'; and 'LED Indicator' with two groups of radio buttons. The first group, 'Power/Ethernet LED', has 'Off' and 'On' options, with 'On' selected. The second group, 'System Status LED', has four options: 'LED on when camera is on' (selected), 'LED on during camera access', 'LED off during camera access', and 'LED always off'. At the bottom are 'OK' and 'Cancel' buttons.

Basic settings may be accessed under **General > Basic Settings**. The following settings can be made:

- **Host Name:** by default set to "model name + MAC address"; displays on the center of the main page. Users may replace the default name with a new name consisting of alphanumeric characters, spaces and the ":" character.
- **Camera Name:** by default set to "model name"; after selecting "Camera Name" from **Settings > Video & Audio > Basic Settings**, the Camera Name will show on the display. Users may replace the default name with a new name consisting of alphanumeric characters, spaces and the ":" character.
- **Power/Ethernet LED:** turns on or off the power and Ethernet LEDs indicator on the rear of the camera.

- **System Status LED:** changes the behavior of the status LED on the front of the camera. There are four possible behaviors:
  - **LED on when camera is on** - LED default on, flashing during camera access.
  - **LED on during camera access** - LED default off, flashing during camera access
  - **LED off during camera access** - LED default on, off during camera access
  - **LED always off** - LED always off

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## User Account

The User Account section, found under **General > User Account**, controls the user account information and privileges.

The screenshot shows a web interface for user account management. The top navigation bar includes 'Live View', 'Settings', 'Logout', and 'Help'. The user is logged in as 'admin' on '2011-07-05 09:43:25'. The left sidebar shows a tree view with 'General' selected, containing 'Basic Settings', 'User Account', 'Date & Time', 'Network', 'Video & Audio', 'PTZ', 'Recording', 'Event Notification', and 'System'. The main content area is titled 'General > User Account' and contains two sections: 'User Account' and 'User Login Settings'. The 'User Account' section has a table with two columns: 'User Name' and 'User Group'. It lists 'admin' as Administrator and 'guest' as Operator. Below the table, it states 'Maximum number of administrators/operators is 10.' and provides 'Add', 'Edit', and 'Remove' buttons. The 'User Login Settings' section has a checkbox for 'Enable access without login' and a text field for 'Maximum number of simultaneous viewers limited to:' with the value '10' and a range '[1..10]'. 'OK' and 'Cancel' buttons are at the bottom.

User Name	User Group
admin	Administrator
guest	Operator

Maximum number of administrators/operators is 10.

Buttons: Add, Edit, Remove

**User Login Settings**

☐ Enable access without login

Maximum number of simultaneous viewers limited to:  [1..10]

Buttons: OK, Cancel

There are two pre-configured accounts:

- **admin** - This is the default administration account, and cannot be deleted.
- **guest** - This is an account with only live view capability.

There are also two basic settings under user account settings:

- **Enable access without login** - Checking the checkbox will allow users to view the camera stream without having to login.
- **Maximum number of simultaneous viewers limited to** - Enter a number from 1 to 10 in this field to limit the number of users that can view the live view stream for this camera. This option will only be displayed once you add an account.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Adding Accounts

In **General**> **User Account** under the **User Account** heading, click on “Add”.

Up to 10 accounts can be added to the system.


A screenshot of a software dialog box titled "Add User Account". The dialog has a light blue header bar with the title. Below the header, there is a sub-header "User Account" with a blue underline. The main area contains four input fields: "User Name:" with the text "test1", "User Group:" with a dropdown menu showing "Administrator", "Password:" with a masked field of dots, and "Confirm password:" with a masked field of dots. At the bottom, there are two buttons: "OK" and "Cancel".

All User Names and Passwords must be combinations of alphanumeric characters, “:”, “-“, “\_” between 4 and 20 characters in length, and must begin with an alphabet letter. Fill out the following fields:

- **User Name** - The identifier name used to login to the system.
- **User Group** - The system allows for 2 types of users.
  - **Administrator** - Administrators have full access privileges.
  - **Operator** - Operators can only access the live view page.
- **Password** - A passkey used to control user access. The password must be a combination of alphanumeric characters, “:”, “-“, “\_” between 4 and 20 characters in length, and must begin with an alphabet letter. This password should be retyped in the **Confirm password** field, to ensure that the correct key is saved.

Click **OK** when finished to add the user to the system.

## Editing Accounts



In **General**> **User Account** under the **User Account** heading, select an existing account by clicking on the account entry. The entry will be highlighted in yellow. Clicking **Edit** will allow you to change the following fields:

- **User Group** - The system allows for 2 types of users.
  - **Administrator** - Administrators have full access privileges.
  - **Operator** - Operators can only access the live view page.
- **Password** - A passkey used to control user access. The password must be a combination of alphanumeric characters, “:”, “-”, “\_” between 4 and 20 characters in length, and must begin with an alphabet letter. This password should be retyped in the **Confirm password** field, to ensure that the correct key is saved.

Click **OK** when finished to save any changes.

**Note:** Only accounts that are not currently logged-in can be edited.

## Deleting Accounts

In **General**> **User Account** under the **User Account** heading, select an existing account by clicking on the account entry. The entry will be highlighted in yellow. Click **Remove** and, when prompted to confirm deletion, click **OK** to remove the account.

## Date & Time

Date and time settings can be accessed at **General > Date & Time**.

The screenshot displays the 'General > Date & Time' configuration page. On the left is a sidebar menu with options: General (selected), Basic Settings, User Account, Date & Time, Network, Video & Audio, PTZ, Recording, Event Notification, and System. The main content area is titled 'General > Date & Time' and includes the following sections:

- Current Date & Time:** Shows 'Date: 2011-07-01' and 'Time: 15:47:21'.
- Time Zone Settings:** Features a dropdown menu for 'Time Zone' currently set to '(GMT +8:00) Beijing, Perth, Singapore, Hong Kong, Taipei'.
- Time Settings:** Contains three radio button options:
  - ☐ Synchronize with NTP server (Periodically synchronize clock with Internet servers): Includes an 'NTP server' text field with the value '64.236.96.53'.
  - ☐ Manual Update: Includes 'Date' and 'Time' text input fields.
  - ☒ Synchronize with Computer Time: Includes 'Date' and 'Time' text input fields, with 'Date' set to '2011-07-01' and 'Time' set to '15:47:24'.
- Day Light Saving:** Includes a checkbox for 'Enable Day Light Saving' (unchecked). Below it are 'Start Time' and 'End Time' settings, each with dropdowns for Month, Day, Hour, and Minute, all currently set to January 1, 00:00.

*Current Date & Time* displays the current system date and time.

### Time Zone Settings

The time zone can be set using the dropdown menu. This menu is only applicable when selectable when **Synchronize with NTP Server** is chosen under **Time Settings**.

### Time Settings

There are 3 ways to set the system time:

- **Synchronize with NTP server** - NTP is a protocol for synchronizing the system clock to an external server. If this option is chosen, enter the IP address of a known NTP server in the **NTP Server** field. You must also choose the appropriate time zone under **Time Zone Settings**.
- **Manual update** - Updates the time manually. Choose the appropriate date and enter a time for the system.
- **Synchronize with computer time** - Synchronizes the time with the computer's internal clock.

### **Day Light Saving**

Users can set the Day Light Saving Time by ticking on **Enable Day Light Saving**.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Network

The network settings, including network configuration, port configuration, and universal plug and play (UPnP) settings are used to configure camera connectivity. These settings are found under the **Settings > Network** context.

The screenshot shows a web interface for network configuration. At the top, there is a navigation bar with 'Live View', 'Settings' (highlighted), 'Logout', and 'Help'. On the right of the bar, it says 'admin 2011-07-01 15:39:24'. A left sidebar contains a tree view with 'General', 'Network' (expanded), 'Port Settings', 'UPnP', 'Video & Audio', 'PTZ', 'Recording', 'Event Notification', and 'System'. Under 'Network', 'Network Configuration' is selected. The main content area is titled 'Network > Network Configuration' and contains three sections: 'IP & DNS Settings', 'PPPoE Settings', and 'DDNS Settings'. In 'IP & DNS Settings', 'Use fixed IP address' is selected. Fields for IP address (61.218.83.87), Subnet mask (255.255.255.240), Default Gateway (61.218.83.81), Primary DNS (168.95.1.1), and Secondary DNS are present. 'PPPoE Settings' has an unchecked 'Enable PPPoE' checkbox and fields for User Name, Password, and Confirm Password. 'DDNS Settings' has an unchecked 'Enable DDNS' checkbox and fields for DDNS Server (a dropdown), Host Name, User Name, and Password.

### Network Configuration

These settings are used to configure basic network access for the camera. They are found under **Network > Network Configuration**.

Most of these settings vary with your specific hardware setup; therefore the defaults are set for common SOHO level usage. If you are using the camera in an enterprise environment, please check with your IT department to determine the correct settings for this section.

### IP & DNS Settings

These settings are used to determine the IP address of the network camera.

- **Get IP address automatically** - Automatically acquires IP address from a DHCP service. This is the default setting.
- **Use fixed IP address** - Sets a fixed IP address. You must also manually fill in IP address, Subnet mask, Default gateway, Primary DNS, and

Secondary DNS fields. The network camera can be connected to the network upon completion.

### PPPoE Settings

This feature is disabled by default. Connecting to the network using PPPoE (Point-to-Point Protocol over Ethernet) requires a user name and password from your ISP (Internet Service Provider). Select **Enable PPPoE** and fill in valid user name and password to connect the camera to the Internet.

### DDNS Settings

DDNS (Dynamic Domain Name Server) is a protocol that enables the camera to maintain a static connection address, even when its IP changes. Access using this feature is disabled by default.

Connecting using DDNS requires registration on third-party websites for DDNS services. Select desired DDNS service website, check the **Enable DDNS** option, and fill in valid user name and password. You can then access the camera through the registered domain name.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Port Settings

Ports are a software construct used to multiplex the transmission information to and from the camera. They act as separate endpoints within an IP address where software "listens" for incoming information. This section, which can be accessed under **Network > Port Settings**, includes *HTTP Port Settings*, *RTSP Settings* and *RTP Multicast Settings*.

The screenshot displays the 'Network > Port Settings' configuration page. The left sidebar contains navigation links: General, Network (selected), Video & Audio, PTZ, Recording, Event Notification, and System. Under the 'Network' section, there are links for Network Configuration, Port Settings (active), and UPnP. The main content area is divided into three sections: HTTP Port Settings, RTSP Settings, and RTP Multicast Settings. The HTTP section has fields for HTTP Port (80) and LiveView Port (6002). The RTSP section includes fields for Access Name for Stream 1 (stream1), Access Name for Stream 2 (stream2), RTSP port (554), RTP port for video (5500), RTCP port for video (5501), RTP port for audio (5502), and RTCP port for audio (5503), each with a corresponding note. The RTP Multicast section has a checked 'Enable RTP Multicast' checkbox and fields for RTP Multicast Video Port1 (5100), RTP Multicast Audio Port1 (5102), RTP Multicast Video Port2 (5104), RTP Multicast Group Address (239.225.76.55), and RTP Multicast TTL (15).

HTTP Port Settings	
HTTP Port:	80
LiveView Port:	6002

RTSP Settings		
Access Name for Stream 1:	stream1	eq. rtsp://IP address/stream1
Access Name for Stream 2:	stream2	eq. rtsp://IP address/stream2
RTSP port:	554	Note: RTSP port must be a valid port number.
RTP port for video:	5500	Note: RTP port for video must be a valid port number.
RTCP port for video:	5501	Note: RTCP port for video must be a valid port number.
RTP port for audio:	5502	Note: RTP port for audio must be a valid port number.
RTCP port for audio:	5503	Note: RTCP port for audio must be a valid port number.

RTP Multicast Settings	
<input checked="" type="checkbox"/> Enable RTP Multicast	
RTP Multicast Video Port1:	5100
RTP Multicast Audio Port1:	5102
RTP Multicast Video Port2:	5104
RTP Multicast Group Address:	239.225.76.55
RTP Multicast TTL:	15

**Note:** The default port numbers in this section are, for the most part, well-known or commonly known values. We recommend that they not be changed unless there is a specific reason to do so.

### HTTP Port Settings

The **HTTP port** number is used access the camera via the HTTP protocol.

The **LiveView Port** number is used to transmit live-view information.

### RTSP Settings

Real-Time Streaming Protocol (RTSP) is a protocol used to establish and control media sessions between end points.

You may change the access name for stream 1, stream 2, the RTSP port number, the RTP port for video, the RTCP port for video, RTP port for audio, and RTCP port for audio.

**Note:** The RTP port number must be an even number. After entering the RTP port number, the RTCP port number will automatically be set to the RTP port number + 1.

### RTP Multicast Settings

Tick **Enable RTP Multicast** to set up multicast via the RTP protocol. The **RTP Multicast video/audio port and group address** can also be set.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## UPnP

The screenshot shows a web interface for configuring a camera. The top navigation bar includes 'Live View', 'Settings', 'Logout', and 'Help'. The user is logged in as 'admin' on '2010-07-26 13:55:15'. The left sidebar contains a tree view with 'General', 'Network', 'Video & Audio', 'PTZ', 'Recording', 'Event Notification', and 'System'. The 'Network' section is expanded, showing 'Network Configuration', 'Port Settings', and 'UPnP'. The 'UPnP' option is selected, displaying the 'UPnP Settings' page. This page has a checkbox for 'Enable UPnP' which is checked. Below it are two input fields: 'Friendly Name' with the value 'CAM2100' and 'Interval' with the value '100'. A range indicator '[10 Sec - 300 Sec]' is shown next to the interval field. At the bottom of the settings area are 'OK' and 'Cancel' buttons.

Universal plug and play (UPnP) is a protocol that simplifies the implementation of networks by allowing new hardware to connect seamlessly to a network. The settings for this feature can be found under **Network > UPnP**.

To enable UPnP, first check the **Enable UPnP** box. If you wish to change the default values, there are two fields that can be edited.


- **Friendly Name** - An identifier for the camera on the network.
- **Interval** - The time between camera-sent UPnP updates.

Click **OK** to activate UPnP or **Cancel** to abort the changes before you leave the page. Once activated, the camera will be visible to other devices on the network.

**Note:** If the computer does not have UPnP installed, you can add it by going to **Start > Control Panel > Add or Remove Programs**. In the Add or Remove Programs page, select **Add/Remove Windows Components > Networking Services** and click **Details**. Select **UPnP** from the popup window, and **OK** out to install **UPnP** services.

## Video & Audio Settings

Video and audio are the heart of a network camera's functionality. The settings for video and audio can be found under **Settings > Video & Audio**. Under this section, you can access basic video and audio settings, video appearance parameters, video stream settings, as well as audio parameters.



### Basic Settings

Basic settings pertain to simple live-view tweaks. These parameters can be found under **Video & Audio > Basic Settings**.

### Video Orientation

In certain mounting situations, the default video output may not be oriented correctly. This setting allows you to change the orientation of the output video.

- **Flip** - flips the image vertically.
- **Mirror** - flips the image horizontally.

### Text Overlay Setting

The text overlay involves is the text displayed in the black bar at the top of the output screen. You can display multiple text messages at the same time. (Only the camera name will display if the resolution is 160 x 120).

- **Include Date** - Displays the current date.
- **Include Time** - Displays the current time.
- **Camera Name** - Displays the name of the camera.

### Audio Settings

Select the desired button to turn audio from the camera on or off.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Image Appearance Settings

These settings, found under **Video & Audio > Image Appearance**, deal with the video output of the camera. There are two tabs, *Image Attributes* and *Sensor Configuration*, as well as *Advanced Settings*.

### Image Appearance (for CAM4110/4160)

The screenshot displays the 'Image Appearance Settings' window for a camera. The interface is divided into several sections:

- Navigation Bar:** Live View | Settings | Logout | Help
- Left Sidebar:** A list of settings categories including General, Network, Video & Audio (selected), PTZ, Recording, Event Notification, and System. Under 'Video & Audio', there are sub-options: Basic Settings, Image Appearance (selected), Video Streams, and Audio.
- Top Right:** User 'admin' and timestamp '2010-07-26 13:50:07'.
- Main Content Area:**
  - Image Appearance Settings:** A live video feed of a street scene with a timestamp '2010-04-14 14:11:23'.
  - Image Adjustment:** Two tabs: 'Image Attributes' (selected) and 'Sensor Configuration'. It contains four sliders:
    - Brightness: 25
    - Saturation: 43
    - Contrast: 7
    - Sharpness: 15
  - Advanced Settings:** A section with six dropdown menus:
    - Flickerless: On
    - Frequency: 60Hz
    - Shutter mode: Auto
    - Slow Shutter Mode: Off
    - White Balance: AWB
    - Day/Night Mode: Day mode
  - Buttons:** 'OK' and 'Default' buttons at the bottom right.

### Image Attributes


These parameters deal with the image lighting and color. All parameters are values ranging from (0) to (100). Dragging the slider to the right increases the value, while dragging to the left lowers the value. The adjustments will be displayed in real-time in the window to the left of the sliders.

- **Brightness** - Adjusts the brightness of the image.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please turn raise the brightness.

- **Saturation** - Adjusts the saturation of the image.
- **Contrast** - Adjusts the contrast of the image.
- **Sharpness** - Adjusts the sharpness of the image.

## Sensor Configuration



The *Sensor Configuration* can be accessed by clicking on the tab to the right of the *Image Attributes* tab. The following parameters can be changed:

- **AGC Gain** - Automatic gain control (AGC) adjusts the video gain level to a variety of inputs. This setting provides a baseline value for the AGC. Values higher than this will be darkened, and values that are lower will be brightened. AGC should be adjusted so that the area of interest is best lit.
- **Backlight compensation** - Backlight compensation adjusts video gain to automatically correct the exposure of objects that are strongly backlit. This brightens the image, at the cost of overexposing areas of high illumination.

### Advanced Settings

The *Advanced Settings* allow you to make changes to the following parameters:



- **Flickerless** - Reduces flickering caused by the difference in frequency of the system and the environment lighting.

- **Frequency** - Used in conjunction with the flickerless function. The user can choose to compensate for 50Hz or 60Hz lighting.


**Note:** In certain situations, the sensor may experience banding issues. In these cases, please turn the flickerless feature on.

- **Shutter Mode** - Sets the camera shutter mode. Longer shutter times allow more light into the sensor, resulting in a cleaner picture, however longer shutter times can result in motion blur.
  - **Auto** - The camera will automatically change the shutter speed to adjust to the lighting conditions.
    - **Slow Shutter Mode** - Used in conjunction with **Auto** shutter mode. Forces a shutter speed of 1/5s when **Night Mode** is activated.
  - **Manual** - This setting allows users to specify a shutter speed.
    - **Shutter Speed** - The user may choose the following shutter speeds: 1/60s, 1/120s, 1/250s, 1/500s, 1/1000s, 1/2000s, 1/5000s, and 1/10000s.
- **White Balance** - This setting allows users to choose the color balancing method used.
  - **AWB** - Automatically chooses white level.
  - **MWB** - The user must specify the red and blue gain levels to achieve the correct white level.
    - **R Gain** - The gain applied to the red video channel.
    - **B Gain** - The gain applied to the blue video channel.
- **Day/Night Mode** - Sets the day (color) and night (black and white, IR cut filter off where applicable.) Night mode sacrifices color information to produce a clear picture with less light.
  - **Auto** - The camera will determine when the light levels require a switch.
    - **Night Threshold** - The threshold which the camera will switch to night mode.
    - **Day Threshold** - The threshold which the camera will switch back to day mode.
  - **Day mode** - Forces day mode.

- **Night mode** - Forces night mode.
- **Schedule for day mode** - Allows the user to set a time for day/night transitions.
  - **From:** - The time, in hours and minutes, when the camera will be in day mode.
  - **To:** - The time, in hours and minutes, when the camera will switch to night mode.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Image Appearance (for CAM4210/4220/4260)



### Image Attributes


These parameters deal with the image lighting and color. All parameters are values ranging from (0) to (100). Dragging the slider to the right increases the value, while dragging to the left lowers the value. The adjustments will be displayed in real-time in the window to the left of the sliders.

- **Brightness** - Adjusts the brightness of the image.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please turn raise the brightness.

- **Saturation** - Adjusts the saturation of the image.
- **Contrast** - Adjusts the contrast of the image.

## Sensor Configuration




The *Sensor Configuration* can be accessed by clicking on the tab to the right of the *Image Attributes* tab. The following features can be activated or deactivated:

- **Auto White Balance** - Artificial lighting or varied lighting conditions may skew the colors in the video image. **Auto White Balance** will attempt to correct the color balance to a more natural state.
- **Backlight compensation** - Backlight compensation adjusts video gain to automatically correct the exposure of objects that are strongly backlit. This brightens the image, at the cost of overexposing areas of high illumination.
- **AGC Gain** - Automatic gain control (AGC) adjusts the video gain level to a variety of inputs to preserve a correct exposure levels.

## Advanced Settings

The *Advanced Settings* allow you to make changes to the following parameters:



- **Flickerless** - Reduces flickering caused by the difference in frequency of the system and the environment lighting.
  - **Auto** - Automatically determines the compensation frequency.


- **50Hz** - Compensates for 50Hz lighting.
- **60Hz** - Compensates for 60Hz lighting.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please turn the flickerless feature on.

- **Day/Night Mode** - Sets the day (color) and night (black and white, IR cut filter off where applicable.) Night mode sacrifices color information to produce a clear picture with less light.
  - **Auto** - The camera will determine when the light levels require a switch.
    - **Night Threshold** - The threshold which the camera will switch to night mode.
  - **Day mode** - Forces day mode.
  - **Night mode** - Forces night mode.
  - **Schedule for day mode** - Allows the user to set a time for day/night transitions.
    - **From:** - The time, in hours and minutes, when the camera will be in day mode.
    - **To:** - The time, in hours and minutes, when the camera will switch to night mode.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Image Appearance (for CAM4310)



### Image Attributes


These parameters deal with the image lighting and color. All parameters are values ranging from (0) to (100). Dragging the slider to the right increases the value, while dragging to the left lowers the value. The adjustments will be displayed in real-time in the window to the left of the sliders.

- **Brightness** - Adjusts the perceived light intensity of the image.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please raise the brightness.

- **Saturation** - Adjusts the colorfulness of a color relative to its own brightness.
- **Contrast** - Adjusts the overall difference in the light vs. dark areas.
- **Sharpness** - Adjusts the edge contrast of the image.

## Sensor Configuration




The *Sensor Configuration* can be accessed by clicking on the tab to the right of the *Image Attributes* tab. The following parameters can be changed:

- **Backlight Compensation** - Backlight compensation adjusts video gain to automatically correct the exposure of objects that are strongly backlit. This brightens the image, at the cost of overexposing areas of high illumination.

## Advanced Settings

The *Advanced Settings* allow you to make changes to the following parameters:



- **Frequency** - Reduces flickering caused by the difference in frequency of the system and the environment lighting. The user can choose to compensate for 50Hz or 60Hz lighting.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please turn the flickerless feature on.

- **EV Compensation** - Sets how much additional exposure the user wishes to adjust from the automatically calculated value: 0 to 100.
- **Exposure Mode** - Sets how the camera captures images. Longer shutter times allow more light into the sensor, resulting in a cleaner picture, however longer shutter times can result in motion blur.
  - **Auto** - The camera will automatically change the shutter speed and gain to balance between image quality and frame rate when there is insufficient light to preserve both.
    - **Exposure Priority** - The priorities for the auto exposure balancing are determined in the dropdown.
      - **Image Quality First** - The camera lower the shutter speed to preserve the gain level set by the **Gain Control** slider.
      - **Frame Rate First** - The camera will raise the gain rate to preserve the shutter speed specified in the **Shutter Speed** dropdown.
      - **Max Shutter Speed** - users can choose the Max Shutter Speed from 1/30, 1/60, 1/120, 1/1000 and 1/10000.
      - **Min Shutter Speed** - users can choose the Min Shutter Speed from 1/30, 1/60, 1/120, 1/250, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/10000 and 1/100000.


**Note:** (1) After selecting **Frame Rate First**, a new parameter - **Environment** will appear. In this category, Indoor/Outdoor Mode can be chosen. (2) The default setting of Environment and minimum shutter speed for 4310 is Indoor (1/120).

- **Main Gain Control** - The gain control slider determines the maximum amount of gain allowed.

- **Manual** - This setting allows users to specify a shutter speed that the camera will not go below, and gain amount that the camera will not exceed.
- **Day/Night Mode** - Sets the day (color) and night (black and white, IR cut filter off where applicable.) Night mode sacrifices color information to produce a clear picture with less light.
  - **Day mode** - Forces day mode.
  - **Night mode** - Forces night mode.
  - **Schedule for day mode** - Allows the user to set a time for day/night transitions.
    - **From:** - The time, in hours and minutes, when the camera will be in day mode.
    - **To:** - The time, in hours and minutes, when the camera will switch to night mode.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Image Appearance (for CAM4311)



### Image Attributes


These parameters deal with the image lighting and color. All parameters are values ranging from (0) to (100). Dragging the slider to the right increases the value, while dragging to the left lowers the value. The adjustments will be displayed in real-time in the window to the left of the sliders.

- **Brightness** - Adjusts the perceived light intensity of the image.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please raise the brightness.

- **Saturation** - Adjusts the colorfulness of a color relative to its own brightness.
- **Contrast** - Adjusts the overall difference in the light vs. dark areas.
- **Sharpness** - Adjusts the edge contrast of the image.

### Sensor Configuration




The *Sensor Configuration* can be accessed by clicking on the tab to the right of the *Image Attributes* tab. The following parameters can be changed:

- **D-WDR** - Specifies if the wide dynamic range (WDR) function is activated. If activated, the WDR function will attempt to preserve detail at contrast extremes.

- **D-WDR Level**- Specifies the WDR correction level ranging from 1 (least) to 10 (most).

## Advanced Settings



The screenshot displays the 'Advanced Settings' window with the following configurations:


- Frequency:** 60Hz (dropdown menu)
- Denoise Level:** 15 (slider bar)
- White Balance:** AWB (dropdown menu)
- Max Shutter Speed:** 1/30 (dropdown menu)
- Min Shutter Speed:** 1/100000 (dropdown menu)
- AGC:** 50 (slider bar)
- Day/Night Mode:** Day mode (dropdown menu)
- Chroma Suppress:** ON (dropdown menu)
- Chroma Suppress Level:** 75 (slider bar)

- **Frequency** - The user can choose to compensate for 50Hz or 60Hz lighting.
- **Denoise** - Removes video noises.
- **Max Shutter Speed** - Longer shutter times allow more light into the sensor, resulting in a cleaner picture, however longer shutter times can result in motion blur. The user may choose the following shutter speeds: 1/2s, 1/5s, 1/7.5, 1/15s, 1/30s, 1/60s, 1/120s, 1/250s, 1/500s, 1/1000s and 1/10000s.
- **AGC Gain** - Automatic gain control (AGC) adjusts the video gain level to a variety of inputs. This setting provides a baseline value for the AGC. Values higher than this will be darkened, and values that are lower will be brightened. AGC should be adjusted so that the area of interest is best lit.
- **White Balance** - This setting allows users to choose the color balancing method used.
  - **AWB** - Automatically chooses white level.

- **MWB** - The user must specify the red and blue gain levels to achieve the correct white level.
  - **R Gain** - The gain applied to the red video channel.
  - **B Gain** - The gain applied to the blue video channel.
- **Day/Night Mode** - Sets the day (color) and night (black and white, IR cut filter off where applicable.) Night mode sacrifices color information to produce a clear picture with less light.
  - **Auto** - The camera will determine when the light levels require a switch.
    - **Night Threshold** - The threshold which the camera will switch to night mode.
    - **Day Threshold** - The threshold which the camera will switch back to day mode.
  - **Day mode** - Forces day mode.
    - **Chroma Suppress** - Reduces the false color phenomena.
  - **Night mode** - Forces night mode.
  - **Schedule for day mode** - Allows the user to set a time for day/night transitions.
    - **From:** - The time, in hours and minutes, when the camera will be in day mode.
    - **To:** - The time, in hours and minutes, when the camera will switch to night mode.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Image Appearance (for CAM4360/4365)



### Image Attributes


These parameters deal with the image lighting and color. All parameters are values ranging from (0) to (100). Dragging the slider to the right increases the value, while dragging to the left lowers the value. The adjustments will be displayed in real-time in the window to the left of the sliders.

- **Brightness** - Adjusts the perceived light intensity of the image.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please raise the brightness.

- **Saturation** - Adjusts the colorfulness of a color relative to its own brightness.
- **Contrast** - Adjusts the overall difference in the light vs dark areas.
- **Sharpness** - Adjusts the edge contrast of the image.

## Sensor Configuration




The *Sensor Configuration* can be accessed by clicking on the tab to the right of the *Image Attributes* tab. The following parameters can be changed:

- **AGC Gain** - Automatic gain control (AGC) adjusts the video gain level to a variety of inputs. This setting provides a baseline value for the AGC. Values higher than this will be darkened, and values that are lower will be brightened. AGC should be adjusted so that the area of interest is best lit.
- **Backlight Compensation** - Backlight compensation adjusts video gain to automatically correct the exposure of objects that are strongly backlit. This brightens the image, at the cost of overexposing areas of high illumination.
- **WDR (2320/2321)** - Specifies if the wide dynamic range (WDR) function is activated. If activated, the WDR function will attempt to preserve detail at contrast extremes.

- **WDR Level** - Specifies the WDR correction level ranging from 1 (least) to 10 (most).

## Advanced Settings

The *Advanced Settings* allow you to make changes to the following parameters:



The screenshot shows a web interface titled "Advanced Settings". It contains the following parameters and their current values:

- Lens Type:** DC-IRIS (dropdown menu)
- Environment:** Indoor (dropdown menu)
- Frequency:** 60Hz (dropdown menu)
- EV Compensation:** 50 (text input field)
- Exposure Mode:** Auto (dropdown menu)
- Exposure Priority:** Frame Rate First (dropdown menu)
- Max Shutter Speed:** 1/120 (dropdown menu)
- Min Shutter Speed:** 1/30 (dropdown menu)
- Max Gain Control:** A slider control with a value of 40.
- Day/Night Mode:** Day mode (dropdown menu)

- **Lens Type** - Chooses the lens type installed on the camera.
  - **Fix Lens** - A fixed lens is installed, and DC-iris adjustments are not possible.
  - **DC-IRIS** - A lens with an adjustable DC-iris is installed, and connected to the port at the back of the camera.
- **Frequency** - Reduces flickering caused by the difference in frequency of the system and the environment lighting. The user can choose to compensate for 50Hz or 60Hz lighting.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please turn the flickerless feature on.

- **EV Compensation** - Sets how much additional exposure the user wishes to adjust from the automatically calculated value: 0 to 100.
- **Exposure Mode** - Sets how the camera captures images. Longer shutter times allow more light into the sensor, resulting in a cleaner picture, however longer shutter times can result in motion blur.

- **Auto** - The camera will automatically change the shutter speed and gain to balance between image quality and frame rate when there is insufficient light to preserve both.
  - **Exposure Priority** - The priorities for the auto exposure balancing are determined in the dropdown.
    - **Image Quality First** - The camera lower the shutter speed to preserve the gain level set by the **Gain Control** slider.
    - **Frame Rate First** - The camera will raise the gain rate to preserve the shutter speed specified in the **Shutter Speed** dropdown.

**Note:** After selecting **Frame Rate First**, a new parameter - **Environment** will appear. In this category, Indoor/Outdoor Mode can be chosen.

- **Max Shutter Speed** - users can choose the Max Shutter Speed from 1/30, 1/60, 1/120, 1/1000 and 1/10000.
- **Min Shutter Speed** - users can choose the Min Shutter Speed from 1/30, 1/60, 1/120, 1/250, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/10000 and 1/100000.


**Note:** (1) After selecting **Frame Rate First**, a new parameter - **Environment** will appear. In this category, Indoor/Outdoor Mode can be chosen. (2) The default setting of Environment and minimum shutter speed for 3365/4365/4360 is Outdoor (1/1000).

- **Main Gain Control** - The gain control slider determines the maximum amount of gain allowed.
- **Manual** - This setting allows users to specify a shutter speed that the camera will not go below, and gain amount that the camera will not exceed.
- **Day/Night Mode** - Sets the day (color) and night (black and white, IR cut filter off where applicable.) Night mode sacrifices color information to produce a clear picture with less light.

- **Auto** - The camera will automatically choose between day/night mode.
- **Day mode** - Forces day mode.
- **Night mode** - Forces night mode.
- **Schedule for day mode** - Allows the user to set a time for day/night transitions.
  - **From:** - The time, in hours and minutes, when the camera will be in day mode.
  - **To:** - The time, in hours and minutes, when the camera will switch to night mode.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Image Appearance (for CAM4361/4371)



**Image Appearance Settings**

2012-06-01 17:12:01

**Image Adjustment**

**Image Attributes** | **Sensor Configuration**

Brightness: 60

Contrast: 10

Saturation: 65

Sharpness: 50

One Push AF: Near << < > >> Far

Wide Tele

**Basic Settings** | **Advance Settings**

AGC: 50

Exposure: AUTO

Max Shutter Speed: 1/30

Min Shutter Speed: 1/50000

Slow Shutter: ☒ OFF ☐ x2 ☐ x4

Day/Night Mode: Auto mode

Night Threshold: 10 Day to Night (0~254)

Day Threshold: 20 Night to Day (1~255)

### Image Attributes

These parameters deal with the image lighting and color. All parameters are values ranging from (0) to (100). Dragging the slider to the right increases the value, while dragging to the left lowers the value. The adjustments will be displayed in real-time in the window to the left of the sliders.

- **Brightness** - Adjusts the perceived light intensity of the image.

**Note:** In certain situations, the sensor may experience banding issues. In these cases, please raise the brightness.

- **Saturation** - Adjusts the colorfulness of a color relative to its own brightness.
- **Contrast** - Adjusts the overall difference in the light vs dark areas.
- **Sharpness** - Adjusts the edge contrast of the image.

- **One Push AF (One Push Auto Focus) (For CAM4371)** - Focus hold mode that can be automatically readjusted as required by the user (One push AF Trigger) assuming that the required subject is within the focusing limits of the camera lens. Press **Near/Far** button or drag the bar between **Wide** and **Tele** to set the focal lengths, and then press the **One Push AF** button.


## Basic Settings

- **AGC Gain** - Automatic gain control (AGC) adjusts the video gain level to a variety of inputs. This setting provides a baseline value for the AGC. Values higher than this will be darkened, and values that are lower will be brightened. AGC should be adjusted so that the area of interest is best lit.
- **Exposure** - Sets how the camera captures images. Longer shutter times allow more light into the sensor, resulting in a cleaner picture, however longer shutter times can result in motion blur.
- **Max Shutter Speed** - users can choose the Max Shutter Speed from 1/30, 1/60, 1/120, 1/1000 and 1/10000.
- **Min Shutter Speed** -- users can choose the Min Shutter Speed from 1/30, 1/60, 1/120, 1/250, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/10000 and 1/100000.
  - **Slow Shutter** - Slows the shutter speed to 1/2 or 1/4.
- **Day/Night Mode** - Sets the day (color) and night (black and white, IR cut filter off where applicable.) Night mode sacrifices color information to produce a clear picture with less light.
  - **Auto** - The camera will determine when the light levels require a switch.
    - **Night Threshold** - The threshold which the camera will switch to night mode.
    - **Day Threshold** - The threshold which the camera will switch back to day mode.
  - **Day mode** - Forces day mode.
    - **Chroma Suppress** - Reduces the false color phenomena.
  - **Night mode** - Forces night mode.


- **Schedule for day mode** - Allows the user to set a time for day/night transitions.
  - **From:** - The time, in hours and minutes, when the camera will be in day mode.
  - **To:** - The time, in hours and minutes, when the camera will switch to night mode.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Sensor Configuration




- **Black light**
  - **BLC** (Backlight compensation) - Adjusts video gain to automatically correct the exposure of objects that are strongly backlit. This brightens the image, at the cost of overexposing areas of high illumination.
    - **BLC Area View** - Users can choose to view the area for BLC effect. When it is opened, you will see the grids showing on the live view screen.
    - **Position\_X** - Adjusts the position of BLC area by moving it leftwards or rightwards.
    - **Position\_Y** - Adjusts the position of BLC area by moving it upwards or downwards.
    - **Size\_X** - Adjusts the size of BLC area by increasing or decreasing its measure horizontally.
    - **Size\_Y** - Adjusts the size of BLC area by increasing or decreasing its measure vertically.
    - **BLC Level** -



- **HSBLC** (High Suppression Backlight Compensation) - Backlight compensation helps resolve detail in darker areas even when brightly lit objects are in view. Highlight suppression goes further, darkening full white areas to achieve optimum video quality.
  - **HSBLC Grid** - Users can choose to view the areas for HSBLC effect. When it is opened, you will see four squares showing on the live view screen.
  - **HSBLC Area Select** - You can choose among the four squares - Area0, Area1, Area2, Area3 for further managements.
  - **Area (0~3) Display** - You can choose to let the selected HSBLC area be displayed on the live screen or not.
  - **Position\_X(0~3)** - Adjusts the position of the selected HSBLC area by moving it leftwards or rightwards.
  - **Position\_Y(0~3)** - Adjusts the position of the selected HSBLC area by moving it upwards or downwards.
  - **Size\_X(0~3)** - Adjusts the size of the selected HSBLC area by increasing or decreasing its measure horizontally.
  - **Size\_Y(0~3)** - Adjusts the size the selected HSBLC area by increasing or decreasing its measure vertically.
  - **HSBLC Level**

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Advanced Settings



Setting	Value
Frequency:	60Hz
Denoise	On
Denoise Level:	30
White Balance:	AWB
DWDR:	Off
LSC:	On
DEFOG:	Off

- **Frequency** - The user can choose to compensate for 50Hz or 60Hz lighting.
- **Denoise** - Removes video noises.
- **White Balance** - This setting allows users to choose the color balancing method used.
  - **AWB** - Automatically chooses white level.
  - **MWB** - The user must specify the red and blue gain levels to achieve the correct white level.
    - **R Gain** - The gain applied to the red video channel.
    - **B Gain** - The gain applied to the blue video channel.
- **DWDR** - Specifies if the wide dynamic range (WDR) function is activated. If activated, the WDR function will attempt to preserve detail at contrast extremes.
- **LSC (Lens Shading Compensation)** - Lens shading is the reduction in light falling on the image sensor away from the center of the image caused by physical obstructions. To suppress the lens shading effect on the corners is called the lens shading compensation.
- **DEFOG**- Adjusts picture quality during bad weather conditions.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Video Streams (for 41xx/42xx Series)

The configuration for video streams, including resolution, frame rate and image quality parameters can be found under **Video & Audio > Video Streams**.

The screenshot shows the 'Video & Audio > Video Streams' configuration page. The left sidebar has a tree view with 'Video & Audio' selected, showing sub-items: 'Basic Settings', 'Image Appearance', 'Video Streams' (highlighted), and 'Audio'. The main panel is titled 'Video & Audio > Video Streams' and contains two sections: 'Video Stream 1 Settings' and 'Video Stream 2 Settings'. Stream 1 settings include: Video Format (H.264), Video Resolution (SXGA (1280 x 1024)), Video Frames per Second (15), Key Frame Interval (1 sec), and Video Quality Settings (Constant Bit Rate: 4 Mbps, Fixed Quality: Medium). Stream 2 settings include: Normal Mode (selected) and 3GPP Mode (unselected), Video Format (MPEG4), Video Resolution (QQVGA(160x120)), Video Frames per Second (15), Key Frame Interval (1 sec), and Video Quality Settings (Constant Bit Rate: 256 kbps, Fixed Quality: Medium). At the bottom right are 'OK' and 'Cancel' buttons. The top of the interface shows 'Live View | Settings | Logout | Help' and a user/session string 'admin 2010-07-28 13:24:32'.

The page is split into settings for 2 streams. Common settings are:

- **Video format** - The compression format for the video stream.
  - **H.264** - Provides the best compression, and clear picture, but is processor intensive.
  - **MPEG4** - Provides more compression than MJPEG, but loses picture quality.
  - **MJPEG** - Provides minimal compression, with the best picture quality. Each frame is stored as a discrete JPEG. This option is only available in Stream 1.
- **Video Resolution** - Sets the resolution of the video output. The following options are available: 1536P (2048 x 1536, CAM2320 Stream 1 only), 1080P (1920 x 1080, Stream 1 only), SXGA (1280 x 1024, Stream 1 only), 720P (1280 x 720, Stream 1 only), VGA (640x480), QVGA (320x240), QQVGA (160x120, Stream 2 and MPEG4 only).

- **Video Frames per Second** - Sets the number of frames per second. 1, 3, 5, 10, 15, 20, 25, 30 FPS are possible values.
- **Key Frame Interval** - Sets the period between minimally compressed recovery frames that don't require other video frames to decode. 1/4s, 1/2s, 1s, 2s, 3s, and 4s are possible values.
- **Video Quality Settings** - Sets the quality of the video image.
  - **Constant Bit Rate** - In this mode, the camera will maintain a constant bit rate output, regardless of video quality. Bit rates available are dependent on the video resolution chosen, and range from 32 kbps to 10 Mbps.
  - **Fixed quality** - In this mode, the camera will attempt to maintain a constant quality output, up to a maximum bandwidth of 10 Mbps.

There are 2 modes in the *Video Stream 2 Settings*:

- **Normal Mode** - All parameters may be changed.
- **3GPP Mode** - All parameters will default to settings that are compatible with mobile viewing. The default in this case is 5fps QQVGA video, with MPEG4 compression at 128kbps and 10 seconds between key frames. None of the parameters can be changed.

**Video Stream2 Settings**

☐ Normal Mode
 ☒ 3GPP Mode

Video format: MPEG4

Video resolution: QQVGA (160 x 120)

Video frames per second: 5

Key frame interval: 10

Video quality settings

☒ Constant bit rate: 128kbps

☐ Fixed quality: Medium

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Video Streams (for 43xx series)

The configuration for video streams, including resolution, frame rate and image quality parameters can be found under **Video & Audio > Video Streams**.

The screenshot displays a 'Video Stream Settings' dialog box with two sections: 'Video Stream 1 Settings' and 'Video Stream 2 Settings'. Each section contains the following parameters:

- Video Format:** A dropdown menu set to 'H.264'.
- Video Resolution:** A dropdown menu. For Stream 1, it is '1080P(1920x1080)'; for Stream 2, it is 'D1(720x480)'.
- Video Frames per Second:** A dropdown menu set to '20' for Stream 1 and '30' for Stream 2. To the right of each dropdown is a radio button and a text input field with the same value and a range in parentheses (e.g., '(1~30)').
- Key Frame Interval:** A dropdown menu set to '1 sec'.
- Video Quality Settings:** Two radio buttons: 'Constant Bit Rate' (selected) and 'Fixed Quality'.
  - Under 'Constant Bit Rate', there is a dropdown menu set to '6 Mbps' for Stream 1 and '2 Mbps' for Stream 2. To the right is a radio button and a text input field with a value (e.g., '6144' for Stream 1) and a range '(32-10240)kbps'.
  - Under 'Fixed Quality', there is a dropdown menu set to 'Medium'.

At the bottom of the dialog are 'OK' and 'Cancel' buttons.

The page is split into settings for 2 streams. Common settings are:

- **Video format** - The compression format for the video stream.
  - **H.264** - Provides the best compression, and clear picture, but is processor intensive.
  - **MPEG4** - Provides more compression than MJPEG, but loses picture quality.
  - **MJPEG** - Provides minimal compression, with the best picture quality. Each frame is stored as a discrete JPEG. This option is only available in Stream 1.
- **Video Resolution** - Sets the resolution of the video output. The following options are available: 1536P (2048 x 1536, Stream 1 only),

1080P (1920 x 1080, Stream 1 only), SXGA (1280 x 1024, Stream 1 only), 720P (1280 x 720, Stream 1 only), VGA (640x480), QVGA (320x240) , QQVGA(160x120, Stream 2 and MPEG4 only).

- **Video Frames per Second**- Sets the number of frames per second. 1, 3, 5, 10, 15, 20, 25, 30 FPS are possible values. You can also choose to type in the values you want (the range is from 1~30).
- **Key Frame Interval** - Sets the period between minimally compressed recovery frames that don't require other video frames to decode. 1/4s, 1/2s, 1s, 2s, 3s, and 4s are possible values.
- **Video Quality Settings** - Sets the quality of the video image.
- **Constant Bit Rate** - In this mode, the camera will maintain a constant bit rate output, regardless of video quality. Bit rates available are dependent on the video resolution chosen, and range from 32 kbps to 10 Mbps. You can also choose to type in the values you want (the range is from 32~10240).
  - **Fixed quality** - In this mode, the camera will attempt to maintain a constant quality output, up to a maximum bandwidth of 10 Mbps.

There are 2 modes in the *Video Stream 2 Settings*:

- **Normal Mode** - All parameters may be changed.
- **3GPP Mode** - All parameters will default to settings that are compatible with mobile viewing. The default in this case is 5fps QQVGA video, with MPEG4 compression at 128kbps and 10 seconds between key frames. None of the parameters can be changed.

**Video Stream2 Settings**

☐ Normal Mode ☒ 3GPP Mode

Video format: MPEG4

Video resolution: QQVGA (160 x 120)

Video frames per second: 5

Key frame interval: 10

Video quality settings


☒ Constant bit rate: 128kbps

☐ Fixed quality: Medium

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Audio Settings

The audio settings, under **Video & Audio > Audio Settings**, contain parameters dealing with audio coming from the cameras built in mic, or an external microphone.

The screenshot shows a web interface for audio settings. At the top, there's a navigation bar with 'Live View', 'Settings' (highlighted), 'Logout', and 'Help'. On the right of the bar, it says 'admin 2010-07-26 16:51:15'. A left sidebar contains a tree view with categories: 'General', 'Network', 'Video & Audio' (selected), 'PTZ', 'Recording', 'Event Notification', and 'System'. Under 'Video & Audio', there are sub-items: 'Basic Settings', 'Image Appearance', 'Video Streams', and 'Audio' (selected). The main content area is titled 'Video & Audio > Audio'. It has three sections: 'Mute Settings' with a 'Mute:' label and two radio buttons, 'On' and 'Off' (selected); 'Line Selection' with an 'Audio In:' label and one radio button, 'Line In' (selected); and 'Codec Settings' with an 'Audio Codec:' label and a dropdown menu showing 'ADPCM'. At the bottom right are 'OK' and 'Cancel' buttons.

- **Mute** - Selects whether or not to mute the incoming audio from the camera.
- **Audio In** - Selects the source for the camera audio feed. **Line In**, an external source connected to the camera's line-in port, is the only option.

**Note:** For models with built-in microphone, Microphone option can be selected in *Line Selection*.


- **ADPCM Bit Rate** - Adaptive differential pulse-code modulation (ADPCM) is a method for digitally encoding audio signals. Only one bit rate, 32 Kbps, is currently supported. Audio will be encoded at this bit rate.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## PTZ

**Note:** CAM 43xx series do not support PTZ functionalities.

RS-485 is a control standard that is used as a basis for controlling point-tilt-zoom (PTZ) cameras or mounts. The PTZ menu **Settings > PTZ > RS-485**

The screenshot shows a web interface for configuring PTZ settings. On the left is a sidebar menu with options: General, Network, Video & Audio, PTZ (selected), RS-485 Settings (sub-selected), Recording, Event Notification, and System. The main content area is titled 'PTZ > RS-485 Settings'. It contains two sections: 'RS-485 Settings' with a 'Baud Rate' dropdown set to '9600', and 'PTZ Settings' with a checked 'Enable PTZ' box, a 'PTZ Decoder Address' text field containing '1', and a 'PTZ Protocol' dropdown set to 'Pelco-P'. At the bottom are 'OK' and 'Cancel' buttons. The top navigation bar includes 'Live View', 'Settings', 'Logout', and 'Help'. The top right corner shows 'admin 2010-07-26 17:16:02'.

**Settings** allows configuration of the RS-485 controls.

The following parameters are configurable:

- **Baud rate** - The baud rate to be used with the RS-485 device. Options are 2400, 4800, 9600, 19200, 11520 bd.
- **Enable PTZ** - This check box activates PTZ service, allowing PTZ controls to be displayed.
  - **PTZ decoder address** - The address of the PTZ decoder, which decodes commands and turns them into electrical signals to drive the PTZ mechanism. This address is a discreet number based on PTZ decoder's connection.
  - **PTZ protocol** - The protocol used by the PTZ. Two of the most common protocols are supported: Pelco-D and Pelco-P.


Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Recording

The Recording menu, **Settings > Recording**, deals with recording settings and managing recorded video files.

### Recording Basic Settings

Recording basic settings, **Recording > Recording Basic Settings** are parameters which deal with the recording location and scheduling.



The screenshot shows a web interface for 'Recording > Recording Basic Settings'. The top navigation bar includes 'Live View', 'Settings', 'Logout', and 'Help'. The left sidebar lists menu items: 'General', 'Network', 'Video & Audio', 'PTZ', 'Recording' (selected), 'Recording Basic Settings' (active), 'Recorded File Management', 'Event Notification', and 'System'. The main content area is titled 'Recording > Recording Basic Settings' and contains three sections: 'Memory Card Recording' with a toggle for 'Memory Card Recording' (set to 'Off'), 'Manual Record Setting' with a text field for 'Manual Record To:' and a 'Browse' button, and 'Event/Schedule Record Setting' with a toggle for 'Event/Schedule Record To:' (set to 'microSD Card'). At the bottom are 'OK' and 'Cancel' buttons. The top right corner shows 'admin 2010-07-26 17:47:01'.


The following parameters can be configured within this menu:

- **Memory Card Recording** - When turned on, video will automatically be recorded onto the microSD card if the network connection is lost. When a network connection is re-established, recording will switch back to the remote destination. If this feature is turned off, there will be no recording at all when if network connection is lost.
- **Manual Record To** - Defines the path for manual recording. Screenshots and user recordings will be saved in this location.
- **Event/Schedule Record To** - Allows the user to set the destination for event or scheduled recording. Event and scheduled recording settings are found under **Settings> Event Notification**.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Recorded File Management

This section, located at **Recording > Recorded File Management** allows users to manage videos recorded on the microSD cards.



### Locating Video Files

To locate video files from a specific time frame, enter a begin and end time in the **From:** and **To:** fields below, and click **Search**.

Each video file will have an entry containing:

- **Time** - The time the video was recorded, also the filename of the entry: YYYY\_MM\_DD\_HH\_MM\_SS.avi
- **Media Type** - The encoding/compression method
- **Trigger Type** - What type of action triggered this recording eg. if it was alarm recording or scheduled recording.
- **Locked** - The lock state of the alarm.

The video records located will be split into pages. The information on these

- **<<** - Click to go to the first page of the recorded files list.
- **<** - Click to go to the previous page of the recorded files list.
- **>** - Click to go to the next page of the recorded files list.
- **>>** - Click to go to the last page of the recorded files list.
- **Forward To:** - This dropdown can be used to skip to a page number.

You may also narrow the entries displayed by clicking on the **Media Type** column. This will give you the option of choosing *All*, *H264*, *MPEG4*, or *MJPEG* types. The system will only show video files of the format selected.

## Managing Video Files

Once you have located the video files of interest you may select them by checking the box in the leftmost column of the entry. You can also select all displayed entries by checking the box in the header row.

There will be two buttons in each entry:

- **Play** - Plays the video file in local helper application.
- **Download** - Downloads video files. Select one or more video files and click **Download**; Choose location to save the video file(s) onto your local PC.

Other actions that you can perform:

- **Lock/Unlock** - Locks/Unlocks video files. Locked files cannot be removed. Select one or multiple video files and click Lock/Unlock. When a file is locked, the Locked status will display yes.
- **Remove** - Manually deletes stored video files. Select one or more video files and click **Remove** to delete the file(s).

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

**Note:** The video files shown in Recorded File Management are files stored in the microSD card. You can also record live video by clicking the record button in the Live View screen, which will be stored directly into your local computer, and are not managed by this function. Please refer to the section on [Manual Record](#) for more information on this functionality.

## Event Notification

Event Notification settings, found under **Settings > Event Notification**, deal with the event detection, scheduled recording, and notification abilities of the camera.

### Event Server

The event server, which can be configured under **Event Notification > Event Server**, is the communications center of the camera. This section deals with the configuration of E-mail and FTP notifications, as well as remote recording.

The screenshot shows the 'Event Notification > Event Server' configuration page. The left sidebar contains a navigation menu with options: General, Network, Video & Audio, PTZ, Recording, Event Notification (selected), Event Server (selected), Motion Detection, Tampering Detection, DI & DO, Event Settings, and System. The main content area is titled 'Event Notification > Event Server' and contains three sections: Email Settings, FTP Settings, and NAS Settings. The Email Settings section includes fields for Sender Email Address (notify@.com), Recipient Email Address (admin@.com), Server Address (smtp.com), User Name (CAMxNotify), Password (masked with dots), and SMTP Server Port (25). A 'Test' button is located next to the SMTP Server Port field. The FTP Settings section includes fields for Server Address (ftpserv1.com), FTP Server Port (21), User Name (CAMxNotify), Password (masked with dots), and FTP Folder Name (Notifications). The NAS Settings section includes fields for Server Address (maximus.fs1.com), User Name (CAMxNotify), Password (masked with dots), and Folder Name (Notifications).

### Email Settings

Email settings are used to configure e-mail notifications.

- **Sender Email Address** - The return e-mail address for notifications. This should be your notification address.
- **Recipient email address** - The e-mail address notification emails will be sent to. Only one email address can be entered.
- **Server address** - The IP or address of the e-mail server.
- **User Name** - The user name of the notifications e-mail account.
- **Password** - The password of the e-mail account.
- **SMTP Server Port** - the SMTP port of the email server; Default 25.

- **Test** - Click this button to send a test email. E-mails will only be sent if all parameters are entered correctly.

### FTP Settings

FTP settings are used to configure recording to a remote location via the file transfer protocol.

- **Server Address** - The address of the FTP server.
- **FTP Server Port** - The port number of the FTP server; Default 21.
- **User Name** - The user name of the FTP account.
- **Password** - The password of the FTP account.
- **FTP Folder Name** - The name of the folder on the FTP site which video files will be stored in.

### NAS Settings


NAS settings are used to configure recording to network attached storage.

- **Server Address** - The address of the NAS server.
- **User Name** - The user name of the NAS account.
- **Password** - The password of the NAS account.
- **Folder Name** - The name of the CIFS account folder on the server.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Motion Detection

The motion detection functionality of the camera can be found under **Event Notification > Motion Detection**.



## Motion Detection Window Management

To detect motion, first a detection window must be created. First click the *Window Settings* tab to enter the window configuration, and click **New** to add a new detection window. A maximum of 3 motion detection windows can be added. Each new window will be created with a default name *Window N*, where *N* is the number of the window. After creating the window, clicking it will select the window. You can drag and resize the window using your mouse. You can also change the following parameters:

- **Window Name** - The name of the motion detection window.
- **Trigger Interval** - The time interval between motion triggers. Options available are: 200 ms , 400 ms, 800 ms, and 1000 ms.
- **Trigger Threshold** - The percentage change in the window before a motion alarm is triggered.
- **Sensitivity** - The sensitivity of the motion box.

Click **Save** to save all settings. Settings of existing windows can also be changed by selecting the window and changing the settings. To delete a window, select a window in and click **Remove**.


After windows are set, you can activate motion detection by checking the **Enable Motion Detection** box.

## Activating and Scheduling Motion Detection

Motion detection is activated by checking the **Enable Motion Detection** box.

**Activate Motion Detection By:** denotes when motion detection will be triggered as an event.

- **Auto** - As long as **Enable Motion Detection** is checked, an event is triggered.
- **Schedule** - Selecting this option allows to manually schedule the



Activate Motion Detection By:

☐ Auto

☒ Schedule

☒ Sun ☐ Mon ☐ Tue ☐ Wed ☐ Thu ☒ Fri ☒ Sat

From: 22:00 To: 06:00 (hh:mm)

times motion detection will be active. Select the days of the week that Motion Detection is active by checking the corresponding boxes, and fill in a start time and end time for motion detection in the **From:** and **To:** boxes.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Triggering a Motion Event

The video displaying on the window is the live streaming video. The *Activity Status Display* tab displays the amount of motion detected in a selected window. By raising the **Sensitivity** of the window the motion values for a given motion, which are shown in yellow, will be higher. When the motion value reaches or crosses the **Trigger Threshold**, denoted by the red line, a motion event will be triggered. Motion alarm handling and notifications can be configured under [Event Settings](#).


## Tampering Detection

Tampering detection is similar to motion detection in that it detects where there is a sudden unexpected change in the whole camera view. Parameters for this feature are found under **Event Notification > Tampering Detection**.

Tampering alarm handling and notifications can be configured under [Event Settings](#).


The tampering detection parameters include:

- **Tampering Detection** - Turns tampering detection on or off.
- **Tampering Sensitivity** - Sets the sensitivity of Tampering Detection.




Options are *Very Low*, *Low*, *Normal*, *High*, and *Very High*. Higher sensitivities can detect more tampering attempts, but also increase the chances that the camera will produce a false alarm.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.



## DI & DO

Digital Input (DI) and Digital Output (DO) stand are used for event triggering. The camera has 1 DO and 2 DI ports. Settings for these ports can be found under **Event Notification > DI & DO**. Conditions for DI and DO triggering, as well as notifications for can be set under [Event Settings](#).



**Note:** CAM4361 does not support DI &DO functionalities.

## Digital Input

The two inputs are listed as Input1 and Input2 and connect to external circuits such as window break detectors. These inputs can be tested by clicking the **Test** button in the input entry.


Each input has a **Normal Status**:

- **Normal Open** - the DI requires a low voltage input, with the following configuration.



It is triggered when it does not receive this input.

- **Normal Close** - the DI requires a high voltage input (+12V), with the following configuration.



It is triggered when it does not receive this input.


- **Off** - DI inputs are closed at all times. The camera will not respond to any signals on this DI.

### Digital Output


The camera can also be configured to send signals through the digital output.

Each output has a **Normal Status**:

- **High** - DO outputs a high voltage when triggered, and is connected to the output circuit in the following manner:



- **Low** - DO acts as a ground when triggered, and is connected to the output circuit in the following manner:



- **Off** - Closes DO output; no signals will be sent.

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Event Settings

Event settings deal with alarm handling and notification, as well as feature scheduling. These settings can be found under the **Event Notification > Event Settings** menu.

The screenshot shows the 'Event Notification > Event Settings' interface. The sidebar on the left lists various settings categories, with 'Event Settings' selected. The main area displays two tables: 'Event List' and 'Schedule List'. The 'Event List' table has columns for Name, Enable, Type, and Actions, with one entry 'test1' that is enabled and triggers actions like Email, FTP, Record, and Trigger DO. The 'Schedule List' table has columns for Name, Enable, Condition, and Actions, with one entry 'schedule1' that is disabled and has a 'Never' condition, triggering an FTP action. Both tables include 'Add', 'Edit', and 'Remove' buttons.

The event handler is rule based. There are lists for both two types of rules:

- **Event List** - Contains rules based on triggered events such as motion detection or DI triggers.
- **Schedule List** - Contains time-based rules.

Each rule has an action list. When the conditions for rule are met, the actions specified by the rule are carried out. Users may perform the following actions in both Event and Schedule lists:

- **Add** - Clicking on the **Add** button adds a new rule to a list.
- **Select** - Clicking on an existing rule selects the rule, highlighting it in yellow.
  - **Edit** - A selected rule may be edited by clicking on the **Edit** button.
  - **Delete** - A selected rule may be deleted by clicking on the **Delete** button.

## Adding/Editing an Event Rule

The Add and Edit screens contain the following triggering actions:

The screenshot shows the 'General' tab of an event rule configuration window. It includes fields for 'Name' (set to 'TriggeredEvent') and 'Set Time Interval Between Triggers (min)' (set to '01:01:01'). Below these is the 'Enable Triggering By' section with radio buttons for 'Always', 'Recurrence Pattern' (selected), and 'Never'. The 'Recurrence Pattern' section has checkboxes for days of the week (Sun, Mon, Tue, Wed, Thu, Fri, Sat) and time range fields 'From' (01:00) and 'To' (03:00). The 'Triggered By' section has checkboxes for 'Motion Detection' (checked), 'On Boot', 'Video Loss & Tampering Detection', 'Disk Full', and 'DI'. The 'Motion Detection' checkbox is accompanied by an 'In Window' dropdown menu showing 'Window 1-e1'.

**Note:** If editing a rule that has not been triggered, the rule will not be triggered after until after editing is complete. If the rule is triggered, any changes will not be applied until the current trigger is resolved.

### General

The following general fields should be filled in:


- **Name** - Specifies the name of the Event.
- **Minimum time interval between triggers** - The time frame in which a subsequent trigger of the same event will be ignored (maximum 23:59:59).

### Enable Triggering By

The next step is to specify the frequency of trigger response. 3 options are available:

- **Always** - The default setting; Triggers event when conditions are met.
- **Recurrence Pattern** - Enables triggering only if conditions are met during a specified time period. To specify the period, select the days of the week that the trigger is active by checking the corresponding

boxes, and fill in a start time and end time for motion detection in the **From:** and **To:** boxes.



The image shows a 'Recurrence Pattern' configuration window. It features a row of checkboxes for days of the week: Sun, Mon, Tue, Wed (checked), Thu, Fri, and Sat. Below this, there are two time input fields labeled 'From:' and 'To:'. The 'From:' field contains '01:00' and the 'To:' field contains '03:00'. A label '(hh:mm)' is positioned to the right of the 'To:' field.

- **Never** - The event is never triggered.

## Enable Triggering By

After the frequency is selected, triggering conditions can be set. Multiple conditions can be set at once. Available options include:


- **Motion Detection** - Trigger when motion is detected.
  - **In Window** - Specifies the detection window that will trigger the event.

Please refer to the section on [Motion Detection](#) for details.

- **On Boot** - Trigger when camera reboots.
- **Video Loss & Tampering Detection** - Trigger when video signal is lost or tampering is detected. Please refer to the section on [Tampering Detection](#) for more detail.
- **Disk Full** - Trigger when the SD disk installed in the camera is full.
- **DI** - Trigger when a DI trigger occurs. For more information please refer to the section on [DI & DO](#).

## When Triggered

The actions to take when trigger conditions are met are configured here.



The image shows a 'Trigger Actions' configuration window. At the top, there is a 'Streams' dropdown menu set to '1'. Below this, there are several checked options: 'Email', 'FTP', 'Record', and 'Trigger DO'. Each checked option has a sub-selection: 'Email' has 'Subject:' and 'Additional Information:' text boxes; 'FTP' has 'Snapshot' (selected) and 'Video' radio buttons; 'Record' has 'Snapshot' (selected) and 'Video' radio buttons. At the bottom, there is a 'Trigger duration:' dropdown menu set to '5 sec'.

The following options are available:

- **Streams** - Selects the stream from which the snapshot or recording will be obtained.

- **Email** - E-mails notifications to the email address specified in the [Event Server](#) settings. If this option is chosen, fill in the following:
  - **Subject** - The subject line of the notification e-mail.
  - **Additional Information** - Contents of the notification e-mail.
  - **Snapshot/Video Clip** - Choose to send a snapshot or video attachment from 5s before to 30s after the trigger.
- **FTP** - uploads a snapshot or video clip to a FTP location specified in the [Event Server](#) settings.
  - **Snapshot/Video Clip** - Choose to upload a snapshot or video file from 5 seconds before to 30 seconds after the trigger. Files are sent as attachments.
- **Record** - Records video to the server specified in the [Event Server](#) settings and the microSD card when triggered. The video clip stored on both remote storage server and local storage is a video file 35 seconds in length (5 seconds before and 30 seconds after the trigger)
- **Trigger DO** - A Digital output signal is sent when triggered.
  - **Trigger Duration** - The length of time that the DO signal is sent. Options are 1, 2, 5, 10, 20 or 30 seconds. For more information please refer to the section on [DI & DO](#).

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

### Adding/Editing a Scheduled Rule

The Add and Edit screens contain the following actions:

The screenshot shows a 'General' settings window. At the top, there's a 'Name' field with the text 'schedule1'. Below it is a 'Set Time Interval (When Activated)' field with the text '01:12' and '(hh:mm)' to its right. Underneath this is a section titled 'Activate Event Time By' with three radio button options: 'Always', 'Recurrence Pattern', and 'Never'. The 'Never' option is selected.

**Note:** If editing a rule that has not been triggered, the rule will not be triggered after until after editing is complete. If the rule is triggered, any changes will not be applied until the current trigger is resolved.

#### General


The following general fields should be filled in:

- **Name** - Specifies the name of the Event.
- **Set Time Interval (When Activated)** - The trigger time of the event (00:00 to 23:59).

### Enable Triggering By

The next step is to specify the frequency of trigger response. 3 options are available:

- **Always** - The default setting; Triggers event when conditions are met.
- **Recurrence Pattern** - Enables triggering only if conditions are met during a specified time period. To specify the period, select the days of the week that the trigger is active by checking the corresponding boxes, and fill in a start time and end time for motion detection in the **From:** and **To:** boxes.




The image shows a configuration window titled "Recurrence Pattern". It contains a row of checkboxes for the days of the week: Sun, Mon, Tue, Wed, Thu, Fri, and Sat. The "Wed" checkbox is checked. Below the checkboxes, there are two text input fields labeled "From:" and "To:". The "From:" field contains "01:00" and the "To:" field contains "03:00". To the right of the "To:" field, the text "(hh:mm)" is displayed.

- **Never** - The event is never triggered.

### When Triggered

The actions to take when trigger conditions are met are configured here.



The image shows a configuration window titled "Trigger Actions". It contains several sections:
 

- Streams:** A dropdown menu with "1" selected.
- Email:** A checked checkbox. Below it are two text input fields labeled "Subject:" and "Additional Information:".
- Snapshot:** A radio button selected over a "Video" radio button.
- FTP:** A checked checkbox. Below it are two radio buttons labeled "Snapshot" and "Video", with "Snapshot" selected.
- Record:** A checked checkbox.
- Trigger DO:** A checked checkbox.
- Trigger duration:** A dropdown menu with "5 sec" selected.

The following options are available:

- **Streams** - Selects the stream from which the snapshot or recording will be obtained.
- **Email** - E-mails notifications to the email address specified in the [Event Server](#) settings. If this option is chosen, fill in the following:
  - **Subject** - The subject line of the notification e-mail.

- **Additional Information** - Contents of the notification e-mail.
- **Snapshot/Video Clip** - Choose to send a snapshot or video attachment from 5s before to 30s after the trigger.
- **FTP** - uploads a snapshot or video clip to a FTP location specified in the [Event Server](#) settings.
  - **Snapshot/Video Clip** - Choose to upload a snapshot or video file from 5 seconds before to 30 seconds after the trigger. Files are sent as attachments.
- **Record** - Records video to the server specified in the [Event Server](#) settings and the microSD card when triggered. The video clip stored on both remote storage server and local storage is a video file 35 seconds in length (5 seconds before and 30 seconds after the trigger)
- **Trigger DO** - A Digital output signal is sent when triggered.
  - **Trigger Duration** - The length of time that the DO signal is sent. Options are 1, 2, 5, 10, 20 or 30 seconds. For more information please refer to the section on [DI & DO](#).

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## System

The system settings, which deal with hardware and firmware parameters, logs, and configuration lists, can be found under **Settings > System**.

### MicroSD Card Management

MicroSD class 2/4/6 cards can be accessed for offline video storage and upgrade purposes. MicroSD installed in the camera can be managed under **System > MicroSD Card Management**.

The screenshot shows the 'System > microSD Card Management' web interface. On the left is a sidebar menu with options: General, Network, Video & Audio, PTZ, Recording, Event Notification, System (selected), and a sub-menu for 'microSD Card Management' containing System Status, System Log, Firmware Upgrade, Reset To Factory Default, and Export/Import & Reboot. The main content area is titled 'System > microSD Card Management' and is divided into two sections. The 'Basic Settings' section displays: 'microSD card Status: no', 'Total Size: 0M', 'Free: 0M', 'Used: 0M', and 'Use(%): 0.00%'. Below this is a 'Format microSD card' section with a 'Password:' input field and a 'Format' button. The 'microSD Card Management' section shows 'Available Recording Time: 0 min', 'Storage Recycle Settings' with 'On' selected (radio buttons for On/Off), and a checked checkbox for 'Max. Duration for Automatic Disk cleanup' set to '12' days.

The status of the current microSD card can be obtained under *Basic Settings*:

- **MicroSD card Status** – If a readable card is present this will show *ready*, otherwise it will display *no*.
- **Total Size** - The size of the card.
- **Free** - The total space left on the card.
- **Used** - The occupied space on the card.
- **Use (%)** - The percentage of the card that has been used.

The user may also enter the administrator password if necessary and click **Format** to format the microSD card.


In *MicroSD Card Management*:

- **Available Recording Time** - Calculates how much recording time is available based on current settings.
- **Storage Recycle Settings** - Turning the function On will clear the microSD card once it is full.
- **Max Duration for Automatic Disc cleanup \_\_ days** - If storage recycling is activated, the card will be cleared when this number of days has elapsed. (100 days max. Locked files will not be cleared).

Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## System Status

The camera status can be found under **System > System Status**.



This section displays useful system information including:


- [Network Configuration](#) defined manually or obtained from DHCP
  - **IP Address**
  - **MAC Address**
  - **Subnet Mask**
  - **Default Router** address
- microSD Card Capacity
- Camera System Information
  - **Boot Loader** Version
  - **Firmware** Version

Clicking on the **Email** button will send the system status information out to the notification e-mail address specified in [Event Server](#) for troubleshooting or reference purposes.

## System Log

The system log, **System > System Log**, provides a log for system messages and events. The log lists important information such as login information, changes to camera settings (both successful and unsuccessful), triggered events, and error messages.

This information can be very useful in the event of a camera failure or unauthorized entry.




Clicking **Email** will send the log out as an email the notification e-mail address specified in [Event Server](#); Clicking **Download** will begin the browser download process to download the log to the local PC.

## Firmware Upgrade

Upgrading with a firmware file on a PC:

1. Power ON the device.
2. Connect to the camera through a web browser and go to **System >**

### Firmware Upgrade.



3. Choose “Specify the firmware to upgrade”. Click Browse...and locate the file [cam number]fw.
4. Select **Keep customized configuration** to keep current configuration settings, or **Upgrade all configurations** to clear all settings back to factory defaults.
5. Click **Upgrade** to start the upgrade. Upon completion of firmware upgrade, the camera will reboot (you will be logged off).
6. The LED will flash amber during the firmware upgrading. The camera will start reboot after firmware upgrade completed.
7. When the LED indicator turns green, the firmware is upgraded successfully.

From microSD/SDHC card:

1. Save the firmware file to a microSD/SDHC card with the file name [cam number]fw.
2. Power off the device.
3. Insert the microSD/SDHC card with the [cam number]fw file into the slot in the rear of the camera.

4. Power on the device and firmware upgrade will start automatically. The status LED flashes in amber during the upgrade.
5. The camera will start reboot after firmware upgrade completed. Remove the microSD/SDHC card from the slot. When LED turns green, firmware upgrade is completed.

**Note:** A microSD/SDHC card with at least 13MB free space is required for firmware upgrade. The device will enter firmware upgrade mode again if the microSD/SDHC card is not removed.

### Emergency Recovery Procedure

If the status LED shows steady amber for over 1 minute, the camera will become unresponsive and the upgrade process may have failed. Please contact with your dealer for technical support.


### Resetting to Factory Default Settings

To reset the device to the factory default settings:

1. Make sure the device is in operation mode.
2. Using a needle or similar object to press and hold the Reset button until the camera restarts (about 2 seconds). The status LED will change to amber during startup.
3. When the Status Indicator changes to back to Green (which may take up to 1 minute), the process is complete. The default IP address is 192.168.88.10 if not assigned by a DHCP server.

**Note:** Resetting to the factory default settings using the Reset button will cause all parameters (including the IP address) to be reset. To reset the unit without changing parameters, disconnect and reconnect the power connector.

Camera resets can also be performed under **System> Reset To Factory Default**.




There are 2 types of reset. You can either reset all settings and configurations, or you can choose to keep the Network configuration, and reset all other settings and configurations.

Click **OK** after choosing a reset option to perform a reset.

Alternately, you may press the “Reset” button on the bottom of the camera to perform a complete reset of the camera (no configurations retained). To reset the camera by pressing the “Reset” button on the bottom of the camera, press and hold the “Reset” button for 3 seconds. During this time, the LED indicator in front of the camera will blink in red.

## Export/Import & Reboot

In certain situations it may be necessary to restart your network camera (network settings changed, DHCP added, etc). The settings under **System > Export/Import & Reboot** allow you to restart the camera.



This menu also contains options to export configuration details (for backup or replication purposes), as well as import configuration details. The following options are available:

- **Restart Camera** - Resets the camera when **Apply** is clicked.
- **Export Configuration** - Export the camera's settings and configurations by clicking **Export**, this will start a browser dialogue to download the configuration.
- **Import Configuration** - Imports previously exported camera settings. The field should contain the path for the camera configuration file. Click **Browse**: to browse your PC for the configuration file. Click **Apply** to import the settings.

# Chapter 5. Configuration through the IP Utility

Camera configurations can be done through web interface and IP Utility.

\*\*For IP Utility, please look into [this chapter](#); for web interface, please refer to [Chapter 4](#).

		Web Interface	IP Utility
General	Basic Settings	V	X
	User Account	V	X
	Date & Time	V	X
Network	Network Configuration	V	Set IP Only
	Port Settings	V	X
	UpnP	V	X
	Wifi Setting (CAM1300/1311 Only)	V	X
Video & Audio Settings	Basic Settings	V	X
	Image Appearance Settings	V	X
	Video Streams	V	X
	Audio Settings	V	X
PTZ	RS-485 Settings/PTZ Settings	V	X
Recording	Recording Basic Settings	V	X
	Recorded File Management	V	X
Event Notification	Event Server	V	X
	Motion Detection	V	X
	Tampering Detection	V	X
	DI & DO	V	X
	Event Settings	V	X
System	MicroSD Card Management	V	X
	System Status	V	V
	System Log	V	X
	Firmware Upgrade	V	V
	Resetting to Factory Default Settings	V	X

	Export/Import	V	V
	Reboot	V	V
Camera Search		X	V
Login		V	V
Properties		X	V
Delete from Tool		X	V
Clearing and Setting Status		X	V
Camera Group Actions		X	V
Focus Tool		X	V


## 5.1. Overview

The IP Utility is a set of tools for network cameras. It includes tools to create, modify, delete and manage groups within the camera; The IP Camera Utility also provides tools to perform simple connectivity configuration, firmware upgrades and reboot operations. The utility is intended to simplify the configuration and management of multiple cameras.


## 5.2. Installing the IP Utility

Install the IP Utility with the following steps:

1. Start SearchToolInstall.exe to begin the utility installation dialog:



2. Click **Next** to continue with installation.



3. Fill in the **Folder** field to specify the installation path. Clicking **Browse...** pulls up a file system browser. Clicking **Disk Cost** will display free space and the space the utility will take up on disks.
4. Choose if you wish to install the application for the current user only (**Just me**) or all users on this computer (**Everyone**).
5. Click **Next** to continue. The system will respond with a ready screen. Click **Next** again. The system will respond by displaying installation progress.
6. You may click **Cancel** at any time before finishing introduction, or **<Back** if it is available to cancel or jump back a step. Click **Close** when after installation is complete. The software is ready to use at this point.

## 5.3. IP Utility Basics


### Starting the IP Utility

To start the IP Utility, double-click the **IP Utility** shortcut on your desktop or go to **Start > Program Files > IP Utility> IP Utility**.

**Note:** On startup, the utility will automatically scan for IP Cameras on the same subnet as the computer. In some cases this may result in longer wait times.

### IP Utility Main Screen

The IP Utility main screen is divided into 3 sections:



1. **Camera Group Display** - displays group details
2. **Camera Detail Display** - displays camera details
3. **Function Buttons and Menus** - this section contains alternative access methods for functions that can be done within the Camera Group and Camera Detail Displays. This manual does not discuss this section separately.

### Exiting the IP Utility

To exit the IP utility, click the X button on the top right corner of the screen or choose **File > Exit** from the menu bar.


## 5.4. Camera Actions

This section displays camera information, including the IP, Name, Model, MAC Address, Status and Network Mask.

### Search

Search updates the details for the cameras listed, as well as locates any new cameras connected on the same subnet. The search is performed every time the IP utility starts. To perform search again:

1. Click the **Auto Search** button or click **Camera > Search** in the menus. The search will begin, and a status bar will display the search progress.




**Note:** The search may take up to 2 minutes, depending on your network configuration.


### Login

Before performing camera actions, most cameras require that proper login credentials are supplied. To login to a camera:

1. Right click the camera you wish to set. Select **Login** from the popup, the system responds with the *Login* window. Alternatively, click the camera entry and choose **Login** from the **Camera** menu.



2. Fill in the user name and password.



A 'Login' dialog box with a blue title bar and a close button (X). It contains four input fields: 'User Name:', 'Password:', 'HTTP Port:' (with '80' entered), and 'Stream Port:' (with '6002' entered). At the bottom are 'OK' and 'Cancel' buttons.


3. Click **OK** to set the username and password.

**Note:** To perform further configuration, please make sure that the User set here has administrator privileges. The default Username/Password for cameras is admin/admin.


## Properties

The properties of a camera can be viewed by following these steps:

1. Select a camera by checking the box in the first column of its listing.
2. Right click the camera and select **Properties**, or select **Camera > Properties** from the menu bar.



The *Camera Information* popup will display with camera details.



**Camera Information**

IP: 172.18.6.57

Status: OK

DHCP: Yes

MAC: 00D0236009E8

Name: CAM2321

Network: 255.255.254.0


Model: CAM2321

Firmware: 1.4.A10T

OK Cancel


## Delete from Tool

1. Select one or more cameras by checking the box in the first column of their listing.
2. Right click the camera(s) which you want to delete from the tool and select **Delete from Tool**. The camera will be removed from the listings.



## Select All


In a group context, right clicking a camera, and selecting **Select All** will select all the cameras in the group.



## Rebooting Camera

In certain cases it may be necessary to reboot the camera. To do this:

1. Select a camera by checking the box in the first column of its listing.
2. Click the **Reboot** button or select **Camera > Configuration > Reboot** from the menu bar.




The camera will reboot. If further configuration is needed, perform the **Login** function again after the reboot is completed.


## Set IP

The IP Address of a camera can be set by following these steps:

1. Click the **Set IP** button.




2. You can choose to obtain an IP address from DHCP or assign a fixed IP.



3. Select one or more cameras by checking the box in the first column of their listing. Click **Select All**.

4. A *Login* window will pop up. Fill in the user name and password. Click **OK**.




Click **OK** to save or **Cancel** to abort the changes before you leave the page.

## Link to Camera Web Interface

### Link to Camera


1. Select a camera by checking the box in the first column of its listing.
2. Click the **Link to Camera** button or click **Camera > Link to Camera** in the menu bar. The camera's live view webpage will open in a browser window.



### Link to Camera User Manager

This function links to the user management page of the selected camera.

1. Select a camera by checking the box in the first column of its listing.
2. Right click the camera and select **User Manager** or click **Camera > User Manager** in the menu bar. The camera's user management webpage will open in a browser window.




## Clearing and Setting Status

### Clear New Status

When a camera is first displayed in the tool, the status column will display the status “New”. These cameras will show up in the *All Devices > New Devices* group. This function clears the status.

To perform this function:

1. Select one or more cameras by checking the box in the first column of their listing.
2. Right click a camera with “New” status, and choose **Device Group > Clear “New” Status** or click **Camera > Device Group > Clear “New” Status** in the menu bar to clear the status.




### Set New Status

This function can be used to set camera(s) to “New” status.

To perform this function, you can:

1. Select one or more cameras by checking the box in the first column of their listing.
2. Right click a camera without “New” status, and choose **Device Group > Set “New” status**, or click **Camera > Device Group > Set “New” status**.



These camera(s) will show up in the *All Devices > New Devices* group. The camera(s) will still be listed under *All Devices > Warning/Errors* if applicable.


## 5.5. Camera Group Actions

The *Camera Group* frame contains a simple tree containing group listings. There are two pre-defined subsections.

- **All Devices** - contains all the cameras in the tool, as well as predefined groups *New Devices* and *Warnings/Errors*
- **MyGroup** - contains only user defined groups.


### Add Group

1. Right click the *MyGroup* root, and choose **Add Group** or choose **Add Group** from the **Group** menu.



The system responds with the *Add Group* popup.

2. In the *New Group Name* field, type in a group name.




3. Click **OK** to add the group. The group will appear under *MyGroup*

**Note:** Camera group names can contain upper and lower-case letters, numerals and the \_ symbol. Cameras can belong to more than one group.

### Delete Group

1. Expand *MyGroup* and right-click the group you wish to delete.
2. Choose **Delete Group** to delete the group. Alternatively, click the group and choose **Delete Group** from the **Group** menu.




3. The system will ask to confirm the deletion. Click **Yes** to delete the group.

**Note:** Groups may be deleted, even if they contain cameras.


## Rename Group

1. Expand *MyGroup* and right-click the group you wish to rename.
2. Choose **Rename Group**. Alternatively, click the group and choose **Rename Group** from the **Group** menu.



The *Rename Group* popup appears.

3. Enter a new group name in the *New Group Name* field.





4. Click **OK** to save your changes.

**Note:** Camera group names can contain upper and lower-case letters, numerals and the \_ symbol.


## Move to Group

This function moves the selected camera(s) from a group to another group.

1. From the *Camera Group* window select a group under *MyGroup*.
2. Select one or more cameras from the existing group by checking the box in the first column of their listing.
3. Right click the camera and select **Device Group > Move to Group**, or select **Camera > Device Group > Move to Group** from the menu bar.



4. In the *Select Group* pop-up box select the destination group.





5. Click **OK** to move the selected camera(s) to the group.

**Note:** Cameras can not be moved from groups under *All Devices*.


## Copy to Group

This function copies the selected camera(s) from a group to another group.

1. From the *Device Group* window select a group.
2. Select one or more cameras from the existing group by checking the box in the first column of their listing.
3. Right-click the camera(s) and select **Device Group > Copy to Group**, or select **Camera > Device Group > Copy to Group** from the menu bar.




4. In the *Select Group* pop-up box select the destination group.



5. Click **OK** to copy the selected camera(s) to the group.

## 5.6. Configuration Settings


Configuration can be downloaded and updated by selecting **Camera > Configuration**, or the process can be automated by downloading the configuration from one camera using the **Download Configuration** function, and then using the **Update Configuration** function to upload the changed configuration file.



### Download Configuration

This function downloads a configuration file.


1. Select a camera by checking the box in the first column of its listing.
2. Right-click the camera which you want to download from and select **Configuration > Download Configuration**, or select **Camera > Configuration > Download Configuration** from the menu bar. The *Download Configuration* popup will display.



3. Click the **Browse** button to browse the computer and locate a destination.
4. Click **Download** to download the configuration file to the destination.

## Update Configuration

1. Select one or more cameras by checking the box in the first column of their listing.
2. Right-click the camera(s) which you want to update to and select **Configuration > Update Configuration**, or select **Camera > Configuration > Update Configuration** from the menu bar. The *Update Configuration* popup will display.




3. Click the **Browse** button to browse the computer and locate a configuration file.
4. Click **Update** to upload the configuration file to the camera(s).

## 5.7. Firmware Actions

### Download Firmware

This function links to the user management page of the selected camera.


1. Select a camera by checking the box in the first column of its listing.
2. Right click the camera and select **Maintenance > Download Firmware** or click **Camera > Maintenance > Download Firmware** in the menu bar. A browser window will open to the Camera firmware webpage, where the newest version of the camera firmware can be obtained.



### Update Firmware


Once a new version of the camera firmware is obtained, the firmware can be updated using the following steps:





**Note:** You must be logged into the camera to update the camera firmware.


1. Select one or more cameras by checking the box in the first column of their listing.
2. Click the **Update Firmware** button; right-click the camera(s) which you want to update to and select **Maintenance > Update Firmware**; or select **Camera > Maintenance > Update Firmware** from the menu bar. The *Update Firmware* popup will display.




3. Click the **Browse** button to browse the file system and locate a firmware file.
4. Click **Update** to upload the firmware to the camera(s).

## 5.8. Focus Tool

The Focus Tool is used as a reference for focus precision. Click the **Focus Tool** button to open it.



Information of *Best Focus Value*, *Current Focus Value* and *Focus Percent* will be shown at the bottom of the Focus Tool Window. You can click **Refresh** to get a new data after focus adjustment is done.



**Note:** When the Focus Percent is higher, the focus is more precise.